clearance triangle, authorized traffic sign or device, or any other public

44

45

transportation mechanism.

- (b) Driveway blockage. No sign may block or interfere with the visibility for ingress or egress of a driveway. All signs, except auxiliary signs, if within 20 feet of driveway ingress or egress, shall provide a minimum of 6 feet of clearance between ground level and the bottom edge of the sign.
- 50 (c) Vision triangle. No sign shall be located within a vision clearance triangle.
- **(d)** Road right-of-way setback requirements.
- **1.** No sign shall be located within a road right-of-way.
- **2.** All signs shall be setback not less than 5 feet from the right-of-way line, the property line, or permanent highway easement, whichever is greater.
- **(e)** Side and rear yard setback requirements. All signs shall be setback not less than 5 feet from any side or rear yard, the right-of-way line, property line, or permanent highway easement, whichever is greater.
- **(f)** Billboards may not be located within 300 feet of an existing on-premise sign or within 1,000 feet of other billboard signs.
- **(g)** Off-premise sign may not be installed within the limits of a curve.
- (h) Projecting signs may not be located directly over a public or private street,
 drive or parking area.
 (i) Off-Premise signs may not be located within 300 feet of on-premise
- **(i)** Off-Premise signs may not be located within 300 feet of on-premise 64 advertising signs.
- **(j)** On-Premise Advertising Wall Signs shall be mounted flush against the dwelling or building in which the business is located.
- **(k)** Buildings which contain multiple businesses shall share the maximum wall sign allowance by dividing the maximum area by the number of proposed businesses. All business may be afforded a maximum wall sign of 20 square feet, if greater than the maximum wall sign limit for the building.
 - (I) No sign shall be installed on a roof.
- **(m)** No sign may be located within a permanently protected green space area or mapped wetland area.
- 74 (4) Design standards.

- (a) No sign shall use any word, phrase, symbol, shape, form or character in such manner as to interfere with moving traffic, including signs which incorporate typical street-type or traffic control-type sign designs and colors. No sign may be installed at any location where by reason of its position, wording, illumination, size, shape or color it may obstruct, impair, obscure, interfere with the view of, or be confused with, any official traffic control sign, signal or device.
- **(b)** Signs, as permitted, shall be professionally designed, constructed and installed.
- **(c)** Graphics. The lettering on a sign shall be clearly legible and in scale with the sign surface upon which it is placed.
- **(d)** Materials. Signs shall be constructed of materials which are of appropriate quality and durability.
- **(e)** Smooth sign face. No nails, tacks or wires shall be permitted to protrude from the front of the sign.
- **(f)** Illumination. All externally illuminated signs shall comply with the following 90 standards.

- 91 Light, number and direction. Signs that are illuminated from an external 92 source shall have external lights directed at only the copy area from a downward 93 angle attached to the top of the sign or sign structure. No externally illuminated 94 sign shall be up-lit or utilize light directed from the ground towards the copy area.
 - Glare. Light sources shall be effectively shielded to prevent beams or rays of light from being directed at any portion of a road or right-of-way that are of such intensity or brilliance as to cause glare or impair the vision of the driver of a motor vehicle, or that otherwise interfere with any driver's operation of a motor vehicle.
- 99 All light sources to illuminate signs, internal or external, shall be shielded 100 from all adjacent buildings and rights-of-way. Light sources shall not be of such brightness so as to cause glare hazardous to the motoring public or adjacent 102 buildings.
 - 4. No sign shall use flashing, moving, reflecting, or changing light sources. Illuminated signs or lighting devices shall employ only a light of constant intensity.
 - Electronic message sign design. Changing copy and electronic message signs must meet the following requirements.
- 107 On-premises ground and pylon signs shall be the only type of sign that may 108 incorporate electronic message components to the sign's copy area.
- 109 Electronic message boards are prohibited on the exterior walls of buildings.
- 110 The electronic message shall not be changed more than once every 6 3. 111 seconds.
- 112 Malfunction. In the event of a malfunction in any portion of the electronic 113 message sign, the sign shall be turned off upon malfunction until the malfunction 114 is corrected.
 - Nits. Electronic message sign copy areas shall not exceed a maximum 5. illumination of 5000 nits during daylight hours and 500 nits between dusk to dawn as measured from the sign's face at maximum brightness.
 - Dimming. All electronic message signs shall be equipped with and shall use photosensitive mechanisms to automatically adjust sign brightness and contrast based on ambient light conditions.
 - (5) Maintenance.

96

97

98

101

103

104 105

106

115

116

117

118 119

120

121

122

123

124

125

126

127

- All signs within the jurisdiction of this ordinance shall remain in a state of proper maintenance. Proper maintenance shall be the absence of loose materials including peeling paint, paper or other material, prevention of excessive rust, the prevention of excessive vibration or shaking and the maintenance of the original structural integrity of the sign, frame and other supports, its mounting and all components thereof.
- 128 Signs found to be in violation of the provisions of this section shall be 129 repaired or removed.
- 132 ARTICLE 4. Section 10.803(3)(f) is amended to read as follows:
- 133 10.803 SIGNS ALLOWED WITHOUT A PERMIT.
- 134 (3) Temporary signs.
- 135 Display period. Signs are limited to a period of 60 days two times per year.
- 136 The 60-day periods shall not run consecutively.

ARTICLE 5. Sections 10.804(1), (4), and (6) are amended to read as follows: **10.804 SIGNS ALLOWED WITH A PERMIT.** The following signs may be permitted in certain zoning districts as shown in the following Table 1 subject to the approval of a zoning permit and the sign design limitations applicable to each type of sign.

(1) Table 1: Signs Permitted with a Permit by Zoning District.

	Zoning		Off-				
Zoning district			Premises				
category	District	Wall	Projecting	Ground	Pylon	Electronic	Billboards
		signs		signs <	signs	message	
				8' off	(> 8' off	signs*	
				ground	ground)		
Natural	NR-C <u>**</u>						
Resource &	RE	Р	Р	Р	Р		
Recreational							
Farmland	FP-1			_			
Preservation	FP-35			Р			
	FP-B	Р	Р	Р	Р		
Rural Mixed	AT-35			Р			
Use &	AT-B	Р	Р	Р	Р		
Transitional	AT-5	С		Р			
	RM-8	С		Р			
	RM-16	С		Р			
Rural	RR-1	С		С			
Residential	RR-2	С		С			
	RR-4	С		C			
	RR-8	С		С			
	RR-16	С		C C			
Residential	SFR-	С		С			
	80						
	SFR-1	С		С			
	SFR-2	С		C			
	TFR-	С		С			
	80						
	MFR-	С		Р			
	80						
Hamlet	HAM-	С		С			
	R						
	HAM-	Р	Р	Р			
	М						
Commercial	LC	Р		Р			
	GC	Р	Р	Р	Р	Р	

	HC	Р	Р	Р	Р	Р	Р	
Processing,	RI	Р	Р	Р	Р	Р		
Manufacturing	MI	Р	Р	Р	Р	Р	Р	
& Industrial								
Special Use	PUD	Determined as part of site plan review by Z.A.						

^{*} On-premises ground and pylon signs, are the only types of signs that may incorporate electronic message components to the sign's copy area.

147

148149

150

(4) On-premise ground signs. On-premise ground signs are subject to the area and placement regulations of the following Table 2 and the design standards of this section.

(a) Table 2: Dimension and Location Standards for On-Premise Ground Signs.

Use	Use Zoning District		0-45	mph	46+	mph	Minimur	n Setbacks (ft.)
	District	Permitted Per road	Max	Max	Max	Max	From	From
		frontage	area	heig	area	heigh	lot line	residential
			sq.	ht ft.	sq.	t ft.		district
			ft.		ft.			
Natural	RE	1	32	12	32	16	5	25
Resource &								
Recreational								
Farmland	FP-35	1*	32	12	32	12	5	25
Preservation	FP-B	1*	32	12	64	16	5	25
Rural Mixed	AT-35	1*	32	12	32	12	5	25
Use &	AT-B	1*	32	12	64	12	5	25
Transitional	AT-5	1*	32	12	32	16	5	25
	RM-8	1*	32	12	32	12	5	25
	RM-16	1*	32	12	32	12	5	25
Rural	RR-1	1*	32	12	32	12	5	25
Residential	RR-2	1*	32	12	32	12	5	25
	RR-4	1*	32	12	32	12	5	25
	RR-8	1*	32	12	32	12	5	25
Residential	SFR-	1*	32	12	32	12	5	25
	80							
	SFR-1	1*	32	12	32	12	5	25
	TFR-	1*	32	12	32	12	5	25
	08							
	MFR-	1	32	12	32	12	5	25
	08							

^{**} Subdivision signs are allowed on NR-C zoned lots located within subdivisions.

P = Permitted with a zoning permit.

C = Permitted if associated with a use under an approved conditional use permit.

Conditional use permits may specify additional restrictions on signs.

Hamlet	HAM- R	1	32	12	32	16	4	25
	HAM- M	1	32	12	32	12	4	25
Commercial	LC	1	32	12	64	16	5	25
	GC	1	32	12	64	16	5	25
	HC	1	32	12	64	16	5	50
Processing,	RI	1	32	12	64	16	5	100
Manufacturing & Industrial	MI	1	32	12	64	16	5	100

^{*} Crop signs shall have a maximum size of 3 square feet and be erected to a height not to exceed 10 feet. There shall not be more than one sign per row of crop.

(6) On-premise wall signs. Wall signs are subject to the design standards of the following Table 4.

(a) Table 4: Dimension and Location Standards for Wall Signs.

TABLE 4

151

152153

154

Use	Zoning					Niur	nhar of 9	Signo
Use	District	<u> </u>		mum		nber of S		
	2.54.164			Height (sq. ft.)		Permitted per Building Number of road		
		(sq. ft.) Height (sq. ft.)		frontages on zoning lot				
		0-45	46+	0-45	46+	1 1	2**	3**
		mph	mph	mph	mph*	'	_	
Recreational	RE	100	300	20	50	2	3	4
Farmland	FP-B	100	300	20	50	2	3	4
Preservation				_0		_		•
Rural Mixed	AT-35	100	300	20	50	2	3	4
Use &	AT-5	100	100	20	20	2	3 2	42
Transitional	AT-B	100	300	20	50	2	3	4
Rural Mixed	RM-8	100	100	20	20	2 2	3 2	42
Use &	RM-	100	100	20	20	2	3 2	42
Transitional	16							
Rural	RR-1	32	32	20	20	1	2	42
Residential	RR-2	32	32	20	20	1	2	42
	RR-4	32	32	20	20	1	2	42
	RR-8	32	32	20	20	1	2	42
	<u>RR-16</u>	32	32	20	20	1	2	2
Residential	SFR-	32	32	20	20	1	2	42
	80							
	SFR-1	32	32	20	20	1	2	42
	SFR-2	32	32	20	20	1	2	2
	TFR-	32	32	20	20	2	3	4
	80							
	MFR-	32	32	20	20	2	3	4
	08							

Hamlet	HAM- R	32	32	20	20	2	3	4	
	HAM- M	32	32	20	20	2	3	4	
Commercial	LC, GC, HC	100	300	20	50	2	3	4	
Processing, Manufacturing & Industrial	RI, MI	100	300	20	50	2	3	4	
Special Use	PUD	Determi	ned as pa	rt of site	olan revie	w by Z.	A .		
*	For buildings 6 stories or more in height, a wall sign may also be located within 20 feet of the top of the building.								
**	The maximum size and height of signs on zoning lots with 2 or more road frontages shall be determined by reference to the nearest adjacent road.								

In no event shall there be more than two walls signs on any one side of the building. Wall signs shall be located only on the building containing the business advertised on the sign.

157 158

159

160 161

162

- **(b)** Design standards.
- **1.** Wall Signs. Wall signs shall not project more than 1 foot from the building wall to which it is attached and shall not project above the building wall. Wall signs may be internally or externally illuminated only in the GC, HC and MI zoning districts.
- 163 **2.** Sign Regulations. See Appendix Table 4.

- ARTICLE 6. Sections 10.804(9) (12) are created to read as follows:
- 166 **(9)** Subdivision signs.
- 167 (a) Shall comply with the location standards of this ordinance.
- 168 **(b)** Shall have a maximum size of 32 square feet and be erected to a height not to exceed 6 feet.
- 170 **(c)** Shall be limited to one subdivision sign per subdivision.
- (10) Projecting signs shall have a maximum size of 21 square feet and be
 installed to a height not to exceed 15 feet. Such signs shall be located on the
 building containing the business advertised on the sign. Projecting signs shall not
 extend more than 3 feet from the face of a building and the lowest portion of such
 signs shall not be less than 8 feet above the finished grade of a sidewalk or other
 pedestrian way.
- 177 **(11)** Home occupation signs shall have a maximum size of 2 square feet and shall be located on the premises of the business advertised on the sign.
- 179 **(12)** Limited family signs. A maximum of two on-premise signs are permitted.
- (a) One wall sign shall be limited to a maximum size of 12 square feet erected to a height not to exceed 8 feet. Such sign shall be located on the building in which
- the business advertised on the sign is located.

(b) One ground sign shall be a driveway entrance sign limited to a maximum sizeof 16 square feet and a maximum height of 8 feet.

185

- 186 ARTICLE 7. Section 10.806(2)(a)2. is amended to read as follows:
- 187 **10.806 ADMINISTRATION.**
- 188 **(2)** Applications and Permits.
- 189 **(a)** Required materials to be submitted for sign permit applications:
- 190 **1.** Completed application form.
- 2. Site Plan. The location of all buildings on the lot shall be provided. The locations of all existing and proposed signs shall be provided. Distance of the proposed sign to property lines shall be provided. Dimensions of the property lines shall be provided. Site plan shall be drawn to scale using an architect's scale (i.e. 1/8" = 1'0") or engineers scale (i.e. 1" = 10').

196

197 [EXPLANATION: On January 17, 2019 Dane County adopted a Comprehensive 198 Revision of its Zoning Code. This amendment adopts multiple revisions to the 199 Sign Regulations subchapter of the Zoning Code.]