



- LED CEILING LIGHT (WHITE)
- ⊗ LED CEILING LIGHT (WHITE, RED OR BLUE)
- ⊗ OR ⊗ ON DURING REDUCED MODE
- ⊖ 120 VAC
- ⊖ 120 VAC WITH DUAL USB PORTS
- ⊖ 120 VAC G.F.I.
- ⊖ INVERTER
- ⊖ 12 VDC
- OUTLET IDENTIFICATION COLOR
- 120 VAC (ELECTRONICS/DEDICATED)
- 120 VAC (NON-DEDICATED)
- 120 VAC (HOT/AUTO EJECT/SHORE)
- HDMI HDMI PORT
- ⊖ RJ-45 NETWORK JACK
- ⊖ RJ-11 TELEPHONE JACK
- TV ANTENNA
- SPARE PLATE
- SPEAKER VOLUME
- SWITCH
- MICROPHONE
- TPD INTERIOR INTEL-I-TOUCH PAD
- TPS EXTERIOR INTEL-I-TOUCH PAD
- SURVEILLANCE CAMERA
- EXTERIOR 120 VAC G.F.I.
- AC THERMOSTAT
- ESPAR FURNACE THERMOSTAT
- ALARM SYSTEM CONTROL
- WATER/WASTE TANK LEVEL MONITOR
- CO/SMOKE DETECTOR
- SPEAKER
- BACK-UP CAMERA
- PERIMETER CAMERA

SOME ITEMS SHOWN MAY BE CUSTOMER SUPPLIED OR OPTIONAL. REFER TO SPECIFICATIONS FOR DETAILS.

THIS DRAWING AND THE INFORMATION THEREON IS THE EXCLUSIVE PROPERTY OF LDV, INC. AND IS TO BE USED SOLELY FOR DEVELOPMENT AND MANUFACTURE OF THE PRODUCT SHOWN. ALL RIGHTS RESERVED IN U.S. COPYRIGHT LAW.

REVISIONS			
NO.	DESCRIPTION	DATE	BY
1			
2			
3			
4			
5			
6			
7			

LDV

DANE CTY LIBRARY SERVICE (WI)
S32BOK-35431-22

DRAWN BY: J. RHYNER
PROJECT MGR: X
DATE: 10.28.22
DATE: X

SCALE: 1/2" = 1'-0"
DWG. TYPE: X