$\begin{array}{c}1&2&3&4&5&6&7\\&&9&0&1&1&2\\&1&1&1&1&1&1&1&1\\&1&1&1&1&1&1&2&2&2&2$	Sub. 1 to 2021 OA-018				
	AMENDING CHAPTER 14 OF THE DANE COUNTY CODE OF ORDINANCES, REVISING EROSION CONTROL AND STORMWATER MANAGEMENT ORDINANCE				
	The County Board of Supervisors of the County of Dane does ordain as follows:				
	ARTICLE 1. Unless otherwise expressly stated herein, all references to section and chapter numbers are to those of the Dane County Code of Ordinances.				
	ARTICLE 2. Subchapter II of Chapter 14, Erosion Control and Stormwater Management, is re- codified and amended as follows:				
	CHAPTER 14 EROSION CONTROL AND STORMWATER MANAGEMENT				
	 14.01 Authority. 14.02 Legislative Findings. 14.03 Purpose and Intent. 14.04 Definitions. 14.05 Jurisdiction and Administration. 14.06 Applicability of Requirement for Erosion Control Permits. 14.07 Applicability of Requirement for Stormwater Management Permits. 14.08 Exemptions and Clarifications. 14.09 Preliminary Review Letter. 14.10 Erosion and Stormwater Control Permits and Administration. 14.11 Erosion Control Plan Requirements. 14.12 Stormwater Management Plan Requirements. 14.13 Off-Site Stormwater Management. 14.14 Technical Standards and Specifications. 14.15 Permit Fees. 14.16 Appeals. 14.17 Variances. 14.18 Violations and Enforcement. 14.19 Penalties. 14.20 Interpretation. 14.21 Severability Clause. 14.01 AUTHORITY. This chapter is recommended by the Dane County Lakes and Watershed Commission and adopted by the Dane County Board of Supervisors under the authority of sec. 33.455 of the Wisconsin Statutes.				
44 45 46	14.02 LEGISLATIVE FINDINGS.(1) The Dane County Board of Supervisors, acting upon the recommendation of the Dane				
47	County Lakes and Watershed Commission, finds that construction site erosion and uncontrolled				

4 stormwater runoff from land disturbing activity and land development activities have significant 48 adverse impacts upon regional water resources and the health, safety, property and general 49 50 51 52 53 welfare of the community, and diminish the public enjoyment and use of natural resources. Specifically, soil erosion and stormwater runoff can:

(a) Carry sediment, nutrients, pathogens, organic matter, heavy metals, toxins and other pollutants to regional lakes, streams and wetlands;

- 54 (b) Diminish the capacity of water resources to support recreational and water supply uses and
- 55 a natural diversity of plant and animal life:
- 56 (c) Clog existing drainage systems, increasing maintenance problems and costs;
- 57 58 (d) Cause bank and channel erosion;
 - (e) Increase downstream flooding;
- 59 (f) Reduce groundwater recharge, which may diminish stream base flows and lower water 60 levels in regional lakes, ponds and wetlands;
- 61 (g) Contaminate drinking water supplies;
- 62 (h) Increase risk of property damage and personal injury; and
- 63 Cause damage to agricultural fields and crops. (i)
- 64 (2) The Dane County Board of Supervisors finds that effective sediment and stormwater 65 management depends on proper planning, design, and timely installation of conservation and 66 management practices and their continuing maintenance. 67

68 14.03 PURPOSE AND INTENT.

69 (1) The purpose of this chapter is to set forth the minimum requirements for construction site 70 erosion control and stormwater management that will diminish threats to public health, safety, 71 public and private property and natural resources of Dane County.

72 73 (2) This chapter is intended to regulate construction site erosion and stormwater runoff, to accomplish the following objectives:

74 (a) Promote regional stormwater management by watershed;

75 76 (b) Minimize sedimentation, water pollution from nutrients, heavy metals, chemical and petroleum products and other contaminants, flooding and thermal impacts to the water resources 77 of Dane County; 78 79

- (c) Promote infiltration and groundwater recharge;
- (d) Protect functional values of natural water courses and wetlands;
- 80 Provide a single, consistent set of performance standards that apply to all developments in (e) both the unincorporated and incorporated areas of Dane County;

81 82 Achieve an 80% reduction in sediment load rates to Dane County waters compared to no (f) 83 controls for all new development, a 40% reduction in sediment load rates compared to no 84 controls for all redevelopment and street reconstruction, and a 20% reduction in sediment load 85 rates compared to no controls for existing developments;

86 (g) Ensure no increase in temperature of stormwater post-development in order to protect cold 87 water communities;

88 (h) Ensure no increase in the rate of surface water drainage from sites during or after 89 construction: and

90 91 (i) Protect public and private property from damage resulting from runoff or erosion.

14.04 DEFINITIONS.

92 (1) Affected means that a regulated activity has significantly:

- 93 94 (a) caused negative impacts on water quality or the use or maintenance of land or business; or
- 95 (b) endangered health, safety, or general welfare.
- 96 (2) Agricultural means related to or used for the production of food and fiber including, but not 97 limited to, general farming, livestock and poultry enterprises, grazing, nurseries, horticulture, 98 viticulture, truck farming, forestry, sod production, cranberry productions and wild crop 99 harvesting. Clearing and grubbing of an area or structural development are not agricultural 100 activity.
- 101 (3) Average annual rainfall means measured precipitation in Madison, Wisconsin between 102 March 12 and December 2, 1981.
- 103 (4) Bank erosion means the removal of soil or rock fragments along the banks or bed of a 104 stream channel resulting from high flow after rain events.

105 (5) Best management practice means a practice, technique, or measure that is an effective, 106 practical means of preventing or reducing soil erosion or water pollution, or both, from runoff both

107 during and after land development activities. These can include structural, vegetative or 108 operational practices.

109 (6) Closed watershed means an area that does not have a surface outlet, with water only able to 110 leave through evaporation, infiltration, or mechanical means. For the purposes of this ordinance. 111 the following are considered closed watersheds:

112 (a) Internally drained watersheds that are at least 20,000 square feet in area and at least 1 foot in 113 depth from invert to lowest surface outlet.

114 (b) Watersheds with no surface outlet discharges from a 2-year, 24-hour design storm.

115 (c) Areas that have historically not drained through surface outlets, as determined by the local 116 approval authority.

117 (7) Cold water community means surface waters capable of supporting a community of cold 118 water fish and other aquatic life, or serving as a spawning area for cold water fish species (NR 119 102.04(3)(a), Wisconsin Administrative Code).

120 Connected impervious means an impervious surface that is directly connected to a (8) 121 separate storm sewer or water of the state via an impervious or concentrated flow path.

122 (9) Construction site erosion control means preventing or reducing soil erosion and 123 sedimentation from land disturbing activity.

124 (10) Design storm means a hypothetical rainstorm that occurs with a specified recurrence 125 interval in Dane County. For example, a 10-year, 24-hour design storm defines a rainstorm that 126 occurs over 24 hours, with a recurrence interval of 10 years. The amounts associated with these 127 128 storms are further defined as follows:

(a) 1-year, 24-hour design storm = 2.49 inches over 24 hours duration using the MSE4 NRCS 129 Rainfall Distribution.

130 (b) 2-year, 24-hour design storm = 2.84 inches over 24 hours duration using the MSE4 NRCS 131 Rainfall Distribution.

132 (c) 10-year, 24-hour design storm = 4.09 inches over 24 hours duration using the MSE4 NRCS 133 Rainfall Distribution.

134 (d) 100-year, 24-hour design storm = 6.66 inches over 24 hours duration using the MSE4 NRCS 135 Rainfall Distribution.

136 (e) 200-year, 24 hour design storm = 7.53 inches over 24 hours duration using the MSE4 NRCS 137 Rainfall Distribution.

138 (f) 500-year, 24-hour design storm = 8.94 inches over 24 hours duration using the MSE4 NRCS 139 Rainfall Distribution.

140 (11) Development means any of the following activities:

141 (a) Structural development, including construction of a new building or other structure;

142 (b) Expansion or alteration of an existing structure that results in an increase in the ground 143 surface dimensions of the building or structure;

144 Land disturbing activity: or (c)

145 (d) Creation or expansion of impervious surfaces.

146 (12) Direct conduits to groundwater means wells, sinkholes, swallets, fractured bedrock at the 147 surface, mine shafts, non-metallic mines, tile inlets discharging to groundwater, guarries, or 148 depressional groundwater recharge areas over shallow fractured bedrock.

149 (13) Director means the Director of the Dane County Land and Water Resources Department or 150 his or her designee.

151 (14) Easement means an interest in land owned by another that creates a nonpossessory right 152 to enter and use the land of another and obligates the owner not to interfere with the uses 153 authorized by the easement.

154 (15) Easement holder means the holder of a legally enforceable easement that authorizes the 155 activity on the land for which a permit is sought under this chapter, including all required 156 maintenance and access obligations.

157 (14) Effective infiltration area means the area of the infiltration system that is used to infiltrate 158 runoff and does not include the area used for site access, berms or pretreatment.

159 (15) Erosion (soil erosion) means the detachment and movement of soil or rock fragments by 160 water, wind, ice or gravity.

161 (16) Excavation means any act by which organic matter, earth, sand, gravel, rock or any other

162 similar material is cut into, dug, quarried, uncovered, removed, displaced, relocated or bulldozed 163 and shall include the resulting conditions.

164 **(17)** *Existing development* means buildings and other structures and impervious area existing prior to August 22, 2001.

(18) Fill means any act by which earth, sand, gravel, rock or any other material is deposited,
 placed, replaced, pushed, dumped, pulled, transported, or moved to a new location and shall
 include the resulting conditions.

169 **(19)** *Final stabilization* means that all land disturbing activity has been completed and that a uniform perennial vegetative cover with a density of at least 70% has been established.

171 **(20)** *Financial security instrument* means an irrevocable letter of credit, surety bond, 172 performance bond, certified check, or cashier's check submitted to the local approval authority to 173 assure that requirements of the ordinance are carried out in compliance with approved plans.

- 174 (21) *Green Infrastructure* means practices that use plant or soil systems, permeable pavement or
- other permeable surfaces or substrates, stormwater harvest and reuse, or landscaping to store,
 infiltrate, or evapotranspirate stormwater and reduce flows to sewer systems or to surface waters.
 Green Infrastructure includes, but is not limited to, the following practices: rainwater
- Green infrastructure includes, but is not limited to, the following practices: rainwater
 harvesting/reuse, rain gardens, bioretention systems, infiltration basins, planters that are
 connected to roof drainage, vegetated swales, permeable pavement, green roofs, and rain
 barrels.
- 181 **(22)** *Gully erosion* means a severe loss of soil caused by or resulting in concentrated flow of sufficient velocity to create a defined flow channel.
- 183 (23) *Heavily disturbed site* means a site where an area of land is subjected to significant compaction due to the removal of vegetative cover or earthmoving activities, including filling.
- Hydrologic soil group (HSG) has the meaning used in the runoff calculation methodology
 promulgated by the United States Natural Resources Conservation Service Engineering Field
 Manual for Conservation Practices.
- (25) Impervious surface means any land cover that prevents rain or melting snow from soaking
 into the ground, such as roofs (including overhangs), roads, sidewalks, patios, driveways and
 parking lots. For purposes of this chapter, all road, driveway or parking surfaces including gravel
 surfaces, shall be considered impervious, unless specifically designed to encourage infiltration
 and approved by the local approval authority.
- 193 **(26)** *Infiltration*, for the purposes of this ordinance, refers to any precipitation that does not leave the site as surface runoff. Also known as "stay-on".
- (27) Infiltration system means a device or practice such as a basin, trench, rain garden or swale designed specifically to encourage infiltration, but does not include natural infiltration in pervious surfaces such as lawns, redirecting of rooftop downspouts onto lawns or minimal infiltration from practices such as swales or road side channels designed for conveyance and pollutant removal only.
- (28) Land conservation committee or LCC means the Dane County Land Conservation
 Committee created under sec. 92.06 of the Wisconsin Statutes.
- (29) Land disturbing activity means any land alterations or disturbances that may result in soil
 erosion, sedimentation, or change in runoff including, but not limited to, removal of ground cover,
 grading, excavating, and filling of land.
- (30) Lightly disturbed site means a site where an area of land is subjected to minor compaction
 due to the limited removal of vegetative cover or earthmoving activities.
- (31) Local approval authority means the director in areas under the direct jurisdiction of Dane
 County as described in sec. 14.05(2) and (3). In incorporated areas that have adopted a local
 ordinance under sec. 14.05(3) and are in compliance, the term means the municipal staff, agency
 or contracted entity charged by the local unit of government with responsibility for enforcing
 stormwater and erosion control ordinances.
- (32) Local land division ordinance means any county, city, village or town ordinance adopted
 under chapter 236, Wis. Stats., to regulate the division of land.
- (33) Local zoning ordinance means any county, city, village or town ordinance adopted under sections 59.69, 59.692, 59.693, 60.61, 60.62, 61.351, 61.354, 62.23, 62.231, or 62.234 of the Wisconsin Statutes to regulate the use of land.
- (34) Maximum extent practicable (MEP). A level of implementing best management practices
 in order to achieve a performance standard specified in this chapter which takes into account the
 best available technology, cost effectiveness and other competing issues such as human safety

- 220 and welfare, endangered and threatened resources, historic properties and geographic features. 221 MEP allows flexibility in the way to meet performance standards and may vary based on the 222 performance standard and site conditions.
- 223 (35) New development means development that results in the cumulative increase of 20,000 224 square feet of impervious surface to a site since August 21, 2001. Sites may be a combination of 225 new development and redevelopment.
- 226 (36) Non-erosive velocity means a rate of flow of stormwater runoff, usually measured in feet 227 228 per second, that does not erode soils. Non-erosive velocities vary for individual sites, taking into account topography, soil type, and runoff rates.
- 229 (37) Peak flow means the maximum rate of flow of water at a given point in a channel, 230 watercourse, or conduit resulting from the predetermined storm or flood.
- 231 (38) Pervious surface means any land cover that permits rain or melting snow to soak into the 232 233 ground.
- (39) Plan means an erosion control plan required by sec. 14.06 or a stormwater management 234 plan required by sec. 14.07.
- 235 (40) Plan review agency means the Dane County Land and Water Resources Department, or its 236 successor, in areas under the direct administrative jurisdiction of Dane County as described in 237 sec. 14.05(2). In incorporated areas of Dane County that have adopted a local ordinance under 238 sec. 14.05(3) and are in compliance, the term means the municipal staff, agency or qualified 239 contracted entity charged by the local unit of government with responsibility for reviewing 240 stormwater and erosion control plans under the local stormwater and erosion control ordinance.
- 241 (41) Plat review officer means the county or municipal staff, agency or contracted entity charged 242 by the local unit of government with responsibility for reviewing land divisions, certified survey 243 maps or plats, or any combination thereof, under chapter 236 of the Wisconsin Statutes.
- 244 (42) Permittee means a land owner or easement holder who has applied for a permit under this 245 Chapter and is responsible for the requirements of the permit.
- 246 (43) Post-development refers to the extent and distribution of land cover types after proposed 247 site development.
- 248 (44) Pre-development refers to the extent and distribution of land cover types present before 249 proposed development, assuming that all land uses prior to development are in "good" condition 250 as described in the Natural Resources Conservation Service Technical Release 55, "Urban 251 Hydrology for Small Watersheds" (commonly known as TR-55). Where the cumulative 252 impervious surface created after August 21, 2001 exceeds 20,000 square feet, the pre-253 254 development condition shall be that prior to August 21, 2001.
- (45) Recharge means the portion of the average annual rainfall that infiltrates the soil and 255 becomes groundwater. Recharge does not include evaporation, transpiration, or runoff from the 256 257 site.
- (46) Redevelopment means development that replaces existing impervious surfaces or results in 258 the cumulative increase of less than 20,000 square feet of impervious surface to a site since 259 August 21, 2001 on sites predominately developed as commercial, industrial, institutional of 260 multifamily. Sites may be a combination of new development and redevelopment.
- 261 (47) Runoff curve number (RCN) has the meaning used in the runoff calculation methodology 262 promulgated by the United States Natural Resources Conservation Service Engineering Field 263 Manual for Conservation Practices.
- 264 (48) Sediment means solid earth material, both mineral and organic, that is in suspension, is 265 being transported, or has been moved from its site of origin by air, water, gravity or ice, and has 266 come to rest on the earth's surface at a different site.
- 267 (49) Sedimentation means the deposition of eroded soils at a site different from the one where 268 the erosion occurred.
- 269 (50) Sheet and rill erosion means a loss of soil caused by sheet flow or shallow concentrated 270 flow, and characterized by an absence of channeling or a relatively uniform loss across the 271 exposed upper layer of the soil or shallow irregular scouring of the soil surface.
- 272 (51) Site means the bounded area described in an erosion control plan or stormwater 273 management plan, including areas that are part of a larger common plan of development
- 274 (52) Slope means the net vertical rise over horizontal run, expressed as a percentage, which 275 represents a relatively homogeneous surface incline or decline over the area disturbed.

(53) Soil loss rate means the rate, usually measured in tons per acre per year, at which soil is
 transported beyond the perimeter of a given control site and which occurs as a result of sheet
 and rill erosion. This term does not apply to soil movement resulting from concentrated flow such
 as gully or bank erosion.

280 **(54)** *Stormwater* means the flow of water which results from, and which occurs during and immediately following, a rainfall, snow- or ice- melt event.

282 **(55)** *Stormwater management* means any measures taken to permanently reduce or minimize 283 the negative impacts of stormwater runoff quantity and quality after land development activities.

(56) Stormwater runoff means the waters derived from rains falling or snowmelt or icemelt occurring within a drainage area, flowing over the surface of the ground and collected in channels, watercourses or conduits.

(57) Street reconstruction means removal and replacement of the road subgrade, where existing stormwater conveyance systems are modified.

(58) Structure means any human-made object with form, shape and utility, either permanently or temporarily attached to, placed upon, or set into the ground, stream bed or lake bed.

(59) Unnecessary hardship means that circumstance where special conditions, which were not self-created, affect a particular property and make strict conformity with regulations unnecessarily burdensome or unreasonable in light of the purposes of this ordinance.

295 14.05 JURISDICTION AND ADMINISTRATION.

296 (1) This ordinance applies to all areas of Dane County.

Unincorporated areas. This ordinance shall become effective in all unincorporated areas of
 Dane County on the date of publication. The director, in consultation with the Dane County
 Conservationist, shall be responsible for administration and enforcement of this ordinance.

300 (3) Incorporated areas.

301 (a) Cities and villages wholly or partially in Dane County may assume administration and 302 regulation of soil erosion and stormwater control programs if they have adopted stormwater and 303 erosion control ordinances that include standards at least as restrictive as those described in 304 secs. 14.04, 14.06 - 14.14 and 14.16 - 14.18. Any such ordinance shall supersede any less 305 restrictive or conflicting provision of a minimum standard, ordinance or local regulation previously 306 adopted by that municipality and shall include effective measures for consistent administration 307 and enforcement. Cities and villages shall have the discretion to adopt by ordinance their own 308 equivalent internal procedures for administration of county standards.

(b) Cities and villages that have enacted local ordinances pursuant to par. (a) or entered into
sec. 66.0301, Wis. Stats., intergovernmental cooperative agreements with the county consistent
with this ordinance may assume responsibility for administration and regulation of soil erosion
and stormwater control programs. When a city or village assumes responsibility for
administration and regulation of soil erosion and stormwater control consistent with this
ordinance, references in this chapter to the director shall mean the local approval authority as
designated by the municipal government.

(c) If a municipality does not enact an ordinance pursuant to par. (a) by the effective date of this ordinance, or if the Dane County Lakes & Watershed Commission, after notice and hearing, determines that a municipality has enacted an ordinance that fails to meet the standards of secs.
14.04, 14.06 - 14.12, 14.14 and 14.16 - 14.18, the director shall enforce the provisions of this ordinance within the limits of the municipality. The director shall continue to administer and enforce the provisions of this ordinance until the municipality adopts and enforces an ordinance at least as restrictive as the county ordinance.
(d) If the Dane County Lakes & Watershed Commission, after notice and hearing, determines

(d) If the Dane County Lakes & Watershed Commission, after notice and hearing, determines that a municipality is not providing effective administration and enforcement of an ordinance adopted under this section, it may make a finding of noncompliance with this ordinance. If a municipality is found to be in noncompliance, the director shall administer and enforce the provisions of this ordinance within the limits of the municipality, to the extent necessary to assure compliance. The director shall continue to administer and enforce the provisions of this ordinance until the Dane County Lakes and Watershed Commission rescinds its finding of noncompliance. Where the standards of this ordinance differ or conflict with applicable local land division,
 zoning, shoreland zoning or other applicable local ordinances or state regulations, the more
 restrictive standards shall apply.

334

14.06 APPLICABILITY OF REQUIREMENT FOR EROSION CONTROL PERMITS. Unless
 expressly exempted by sec. 14.08, an erosion control permit under sec. 14.10 shall be required
 and all construction site erosion control provisions of this chapter shall apply, to any of the
 following activities in Dane County:

- 339 (1) Land disturbing activity in excess of 4,000 square feet;
- 340 (2) Land disturbing activity that involves the excavation and/or filling or a combination of excavation and filling, in excess of 400 cubic yards of material;
- (3) Land disturbing activity that disturbs more than 100 lineal feet of road ditch, grass waterway
 or other land area where surface drainage flows in a defined open channel; including the
 placement, repair or removal of any underground pipe, utility or other facility within the cross section of the channel;
- 346 (4) Any new public or private roads or access drives longer than 125 feet;
- 347 (5) Development that requires a plat, as defined in the applicable local land division 348 ordinance(s);
- (6) Land disturbing activity that disturbs less than 4,000 square feet of land, including the
 installation of access drives, that the local approval authority determines to have a high risk of
 soil erosion or water pollution, or that may significantly impact a lake, stream, or wetland area.
 Examples of activities with a high risk of soil erosion or water pollution may include, but are not
 limited to, land disturbance on erodible soil or disturbance adjacent to lakes, rivers, streams or
 wetlands. All such determinations made by the local approval authority shall be in writing, unless
 waived by applicant.
- 356 357

14.07 APPLICABILITY OF REQUIREMENT FOR STORMWATER MANAGEMENT PERMITS.

Unless otherwise exempted by sec. 14.08, a stormwater management permit under sec. 14.10 shall be required and all stormwater management provisions of this chapter shall apply to any of the following activities within Dane County:

- (1) Any development(s) after August 22, 2001 that result(s) in the cumulative addition of 20,000
 square feet of impervious surface to the site.
- 363 (2) Any development that requires a plat, as defined in applicable local land division 364 ordinance(s).
- 365 (3) Any development that requires a certified survey map, as defined in the applicable local land division ordinance(s); for property intended for commercial or industrial use.
- (4) Land disturbing activity in excess of 4,000 square feet on sites developed as commercial,industrial, institutional or multifamily.
- (5) Other land development activities including, but not limited to, redevelopment or alteration of
 existing buildings and other structures, that the local approval authority determines may
 significantly increase downstream runoff volumes, flooding, soil erosion, water pollution or
 property damage, or significantly impact a lake, stream, or wetland area. All such determinations
 shall be made in writing unless waived by the applicant.

375 **14.08 EXEMPTIONS AND CLARIFICATIONS.**

376 (1) The following are exempt from all requirements of this ordinance:

377 (a) Any activity directly related to the planting, growing and harvesting of agricultural crops
 378 except the construction of a building or other structure.

(b) Projects specifically exempted from local erosion control ordinances under state or federal statute. It is the responsibility of the landowner or easement holder to demonstrate such exemption with documentation acceptable to the local approval authority.

382 (2) The following are exempt from the construction site erosion control provisions of sec. 14.06:

(a) One and two-family dwelling units regulated under the Wisconsin Uniform Dwelling Code.
 Land disturbing activity in excess of one (1) acre, or not associated with the construction of a dwelling, are not exempt from this chapter.

386 (b) Projects subject to an approved shoreland erosion control permit under chapter 11.

- 387 (c) Maintenance of existing cropped fields with a prior approved conservation plan.
- 388 (d) Soil conservation, stream and adjacent wetland protection and restoration practices such as 389 terraces, run-off diversions, grassed waterways, cattle and equipment crossings, cattle watering 390 access, water control structures, dikes, ditch plugs, tile breaks and sediment removal 391 catchments, when implemented according to plans and designs approved by the Natural 392 Resources Conservation Service or U.S. Fish & Wildlife Service of the U.S. Department of the 393 Interior, Wisconsin Department of Natural Resources or the Dane County Land and Water 394 Resources Department, provided that any such project involving land disturbing activity equal to 395 or greater than one (1) acre shall also comply with the performance standards in sec. 14.11(3).
- 396 (3) The following are exempt from the runoff rate control standards of sec. 14.12(2)(c):
- 397 (a) Redevelopment.
- 398 (b) Municipal road or county highway projects not exempted under sec. 14.08(1)(b) where all of the following conditions are met:
- 400 **1.** The purpose of the project is only to meet current state or federal design or safety 401 guidelines;
- 402 **2.** Proposed impervious areas are within existing public right-of-way;
- 403 3. All other requirements of sec. 14.12 are met; and
- 404 **4.** The project does not include the addition of new driving lanes.
- 405 (4) The following activities are exempt from the infiltration standards described in s. 14.12(2)(e):
- 406 (a) Redevelopment
- 407 **(b)** New development with less than 10% connected imperviousness, provided the cumulative area of all impervious surface is less than one acre.
- 409 (c) Agricultural facilities and practices.
- 410 (d) Areas where the infiltration rate of the soil is less than 0.6 inches/hour measured at the 411 bottom of the proposed infiltration system where the soil layer is not easily removed or 412 manipulated.
- 413 **(e)** Expansion of municipal or county roads.

415 **14.09 PRELIMINARY REVIEW LETTER.**

- (1) Purpose and intent. A preliminary review letter provides a potential permit applicant with an initial simple evaluation of whether erosion and stormwater control standards can be met for a proposed site, lot layout, construction design. This review is intended to assist applicants in preparing general site plans and other submittals necessary to obtain an erosion control and stormwater permit. A preliminary review letter does not guarantee that an erosion or stormwater control plan will be approved or that a permit will be issued. Erosion and stormwater control plans and permit applications must meet all applicable standards and criteria for approval.
- 423 (2) Application procedure.
- 424 (a) The local approval authority may adopt an application procedure and fees for provision of a 425 preliminary review letter.
- 426 **(b)** The local approval authority may charge a fee to compensate for the cost of the preliminary 427 review letter process.
- 428 (c) Any person may apply for a preliminary review letter by submitting an application that 429 contains the information required by the local approval authority.
- (d) The local approval authority may require a preliminary review letter prior to accepting an application for a zoning permit, petition to rezone or conditional use permit under applicable ordinance(s), or the plat review officer may require a preliminary review letter prior to accepting an application for a certified survey map under applicable local land division ordinance(s) where any of the following apply:
- 435 **1.** The proposal would involve one or more acres within either the current or proposed 436 boundaries of a commercial zoning district;
- 437
 2. Proposed lot or rezone area configuration would necessitate driveways, access roads or
 438 other construction that would clearly require an erosion control plan or stormwater management
 439 plan under sec. 14.06 or 14.07;
- Autural features of the site including, but not limited to, slope, soils, wetlands, or hydrology are such that, in the opinion of the local approval authority, substantial risk of erosion, flooding or other environmental or public safety hazard exists; or, in the opinion of the plat review officer,

443 consultation with plan review agency staff is necessary to determine land suitability requirements444 under local subdivision ordinances.

445 (e) Unless expressly waived by the applicant, decisions by the local approval authority to require
446 a preliminary review letter shall be made in writing and shall detail the reasons why the authority
447 believes there to be a substantial risk of erosion, flooding or hazard.

448

449 14.10 EROSION AND STORMWATER CONTROL PERMITS AND ADMINISTRATION.

450 (1) No activity meeting the criteria described in ss. 14.06 or 14.07 shall occur and no zoning
 451 permit may be issued, until an erosion control and stormwater control permit is issued by the
 452 local approval authority.

- 453 (2) The applicant must provide the following when requesting a permit:
- 454 (a) Completed application form signed by the landowner or easement holder. If the applicant is 455 not the landowner or easement holder, a notarized statement authorizing the applicant to act as 456 agent on behalf of the landowner or easement holder must be provided. By signing the 457 statement, the permittee shall be bound by all requirements of this ordinance and the terms of 458 any permit issued to the applicant. If the applicant is an easement holder or an agent of an 459 easement holder the landowner must be given notice and a copy of the permit application and all 460 supporting documentation. Proof of such notice must be provided with the application. The local 461 approval authority shall provide the landowner with copies of all permits and notifications issued 462 regarding permit applications:
- 463 (b) Fees as required by sec. 14.15;
- 464 (c) Copy of preliminary review letter, as described in sec. 14.09, if applicable;
- 465 (d) If required by sec. 14.06, an erosion control plan meeting all requirements of sec. 14.11;
- 466
 467
 467
 468
 468
 468
 468
 469
 469
 469
 460
 460
 460
 460
 460
 460
 460
 461
 462
 463
 464
 464
 465
 465
 466
 466
 466
 467
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
 468
- 469 (e) If required by sec. 14.07, a stormwater management plan meeting all of the standards of sec. 14.12 and a draft maintenance agreement as described in sec. 14.12(1)(i);
- 471 (f) Copies of permits or permit applications or approvals required by any other governmental 472 entity;
- 473 (g) A proposed timetable and schedule for completion and installation of all elements of
 474 approved erosion control and stormwater management plans and a detailed schedule for
 475 completion of construction.
- 476 **(h)** An estimate of the cost of completion and installation of all elements of the approved erosion control and stormwater management plans.
- 478 (i) Evidence of financial responsibility to complete the work proposed in the plan. The local
 479 approval authority may require a financial security instrument sufficient to guarantee completion
 480 of the project.
- 481 (3) Approval process.
- (a) The local approval authority shall verify that the permit application is complete under sec.
 14.10(2). The local approval authority shall then forward plan(s) to the plan review agency for
 review and approval. Plan review staff shall review the plan(s) for compliance with the standards
 identified in secs. 14.11-14.12. Additional information may be requested at any time to help
 determine ordinance compliance.
- (b) Within the timeframe set by the local approval authority, plan review staff shall either
 approve the submitted plan or notify the local approval authority of any deficiencies. Staff
 engaged in this review and approval process shall be certified where appropriate by the
 Wisconsin Department of Commerce for this purpose.
- 491 **(c)** The local approval authority shall notify the applicant in writing of any deficiency in the 492 proposed plan and the applicant shall be given an opportunity to correct any deficiency.
- 493 (d) Where stormwater practices will be implemented, an affidavit which describes the
- 494 property by legal description, notifying future prospective purchasers of the existence of a
- 495 stormwater permit issued under this ordinance and applicable plan, timetables and potential
- liability imposed by sec. 14.18(3) for failure to bring the property into compliance with this ordinance after patification, shall be recorded with the Dane County Register of Danes prior
- 497 ordinance after notification, shall be recorded with the Dane County Register of Deeds prior to

issuance of an erosion and stormwater control permit. The foregoing information shall also benoted on every plat and certified survey map.

500 (e) Upon approval of the plan review agency, the erosion control or stormwater management 501 permit shall be issued by the local approval authority after the applicant has met all other 502 requirements of this ordinance.

503 (4) Permit conditions.

504 (a) The plan shall be implemented prior to the start of any land disturbing activity and shall be 505 maintained over the duration of the project. Stormwater components of the plan shall be 506 maintained in perpetuity.

507 (b) The permittee is responsible for successful completion of the erosion control plan and the
 508 stormwater management plan. The permittee shall be liable for all costs incurred, including
 509 environmental restoration costs, resulting from noncompliance with an approved plan.

(c) Application for a permit shall constitute express permission by the permittee for the local approval authority to enter the property for purposes of inspection under sec. 14.10(5) or curative action under sec. 14.18(3). If the permittee is an easement holder such entry must be consistent with the terms of the easement. The application form shall contain a prominent provision advising the applicant and landowner of this requirement.

515 (d) All incidental mud-tracking off-site onto adjacent public thoroughfares shall be cleaned up 516 and removed by the end of each working day using proper disposal methods.

517 (e) A copy of the approved permit and erosion control plan shall be kept on the project site, in a 518 place readily accessible to contractors, engineers, local approval authority inspection staff and 519 other authorized personnel.

520 (5) Inspections.

(a) Application for a permit under this ordinance shall constitute permission by the permittee for
 the local approval authority to enter upon the property and inspect during the construction phase
 prior to the inspections pursuant to paragraphs (d) and (f), as necessary to confirm compliance
 with the requirements of this ordinance.

(b) As part of the plan approval process, the local approval authority shall determine the
minimum inspection frequency required to assure compliance. The minimum frequency shall not
be greater than every 30 days. The site shall be inspected by the local approval authority during
the construction phase at the frequency specified.

(c) The permittee shall notify the local approval authority within 10 days after installation of all practices in an approved erosion control plan and achievement of soil stabilization. The permittee shall inspect the site weekly, and prior to every forecasted rain fall of ½ inch or greater.

(d) The local approval authority shall inspect the property to verify compliance with the erosion control plan within 10 days of notification of soil stabilization.

(e) Within 10 days after installation of all practices in an approved stormwater management plan, the permittee shall notify the local approval authority and submit as-built certification to ensure that constructed stormwater management practices and conveyance systems comply with the specifications included in the approved plan. The as-built certification shall include a set of drawings, stamped by a professional engineer, comparing the approved stormwater management plan with what was constructed. Other information shall be submitted as required by the local approval authority.

541 (f) The local approval authority shall inspect the property to verify compliance within 30 days of notification.

543 (g) Maintenance is the responsibility of the permittee, and facilities are subject to inspection 544 and orders for repairs.

545 (6) Permit transfers.

546 (a) When a permittee acts to transfer an interest in property subject to an approved plan prior to
 547 completion of the proposed steps to attain soil stabilization, the permittee must secure approval
 548 from the local approval authority.

(b) When a permittee transfers ownership, possession or control of real estate subject to either
 or both an uncompleted erosion control stormwater management plan, the successor in interest
 to the permittee shall be responsible to control soil erosion and runoff and shall comply with the

552 minimum standards provided in this ordinance.

553 (c) When ownership, possession or control of property subject to an uncompleted erosion 554 control or stormwater management plan, or both, is transferred, the permittee shall notify the new 555 owner (buyer) as to the current status of compliance with notice to the authority, and provide a 556 copy of the erosion control plan or stormwater management plan, or both.

557 (d) Transfers of interest in real estate subject to an approved, uncompleted plan may be 558 conducted consistent with this ordinance under any of the following arrangements:

559 The transferee shall file a new, approved erosion control or stormwater management plan, 1. 560 or both, with the authority:

561 The transferee shall obtain an approved assignment from the authority as sub-permittee to 2. 562 complete that portion of the approved plan regulating soil erosion and runoff on the transferee's 563 property.

564 3. The permittee shall provide the authority with a duly completed and executed continuing 565 surety bond or certified check in an amount sufficient to complete the work proposed in the 566 approved plan; at the time of transfer the permittee may seek to reduce the surety bond or 567 certified check to the appropriate amount to complete remaining work. If the transferor enters into 568 escrow agreements with transferees to complete an approved plan, these funds shall be 569 available to the authority to attain plan compliance. When an approved erosion control plan and, 570 if required, a stormwater management plan is or are not completed as proposed, the authority 571 may use the surety bond to complete remaining work to achieve plan compliance.

572 (7) Plan or permit amendments. Any proposed modifications to approved plans, construction 573 schedules or alterations to accepted sequencing of land disturbing activity shall be approved by 574 the director prior to implementation.

- 575 (8) Timeframe and Expiration:
- 576 (a) Erosion control plan timetables and construction schedules must begin within one year from 577 date of application. 578
 - (b) All permit applications shall expire:
- 579 one year after the applicant is notified of, but does not adequately address, a deficiency, or 1.
- 580 2. three years from date of application, whichever is sooner.
- 581 (c) Erosion control permits shall expire:
- 582 1. upon stabilization date in the approved plan, or
- 583 2. three years after permit issuance, whichever is sooner. 584

14.11 EROSION CONTROL PLAN REQUIREMENTS.

586 (1) Plan materials. Erosion control plans shall include, at a minimum, the following information:

587 (a) property lines, lot dimensions, and limits of disturbed area, including disturbed areas within 588 five (5) feet of the property line:

589 (b) limits of impervious area, including buildings. Include all public and private roads, interior 590 roads, driveways, parking lots, and indicate type of paving and surfacing material;

591 (c) All natural and artificial water features including, but not limited to, lakes, ponds, streams 592 (including intermittent streams), and ditches. The plan must show ordinary high-water marks of 593 all navigable waters, 100-year flood elevations and delineated wetland boundaries. A certified 594 flood zone determination and/or wetland delineation may be required at the applicant's expense;

- 595 (d) areas of natural woodland or prairie;
- 596 (e) cross sections of and profiles of channels, swales, and road ditches;
- 597 (f) culvert sizes:

585

- 598 (g) direction of flow of runoff;
- 599 (h) watershed size for each drainage area;
- 600 (i) design discharge for ditches and structural measures;
- 601 runoff velocities; (j)
- 602 fertilizer and seeding rates and recommendations; (k)
- 603 (I) time schedules for stabilization of ditches and slopes;
- 604 (m) description of methods by which sites are to be developed and a detailed land disturbance 605 schedule including time schedules for stabilization of ditches and slopes;
- 606 (n) provision for sequential steps mitigating erosive effect of land disturbing activity to be
- 607 followed in appropriate order and in a manner consistent with accepted erosion control

- 608 methodology suitable to proposed sites and amenable to prompt re-vegetation, including runoff 609 calculations as appropriate;
- 610 (o) provisions to prevent mud-tracking off-site onto public thoroughfares during the construction period;
- 612 (p) provisions to disconnect impervious surfaces, where feasible;
- 613 (q) provisions to prevent sediment delivery to, and accumulation in, any proposed or existing stormwater conveyance systems;
- 615 (r) copies of permits or permit applications required by any other unit of government or agency;
- 616 (s) existing and proposed elevations (referenced to the North American Vertical Datum of 1988,
- 617 where available) and existing and proposed contours in the area, where deemed necessary;
- 618 (t) any other information necessary to reasonably determine the location, nature and condition 619 of any physical or environmental features of the site.
- 620 (2) Simplified plan materials. Sites meeting the conditions described in sec. 14.10(2)(d)1. may instead provide, at a minimum, the following information:
- 622 (a) Narrative describing the project;
- 623 **(b)** Site plan of known scale that includes property lines, disturbed area limits, impervious area 624 limits (existing and proposed), natural and artificial water features, 100-yr flood plain, delineated
- 625 wetland boundaries, and location of all proposed erosion control practices;
- 626 (c) Contours (existing and proposed);
- 627 (d) Watershed size for each drainage area, including areas draining to the site;
- 628 (e) Provisions to prevent tracking sediment onto public roads;
- 629 **(f)** Provisions to prevent sediment delivery to, and accumulation in, any proposed or existing stormwater conveyance systems;
- 631 (g) Proposed erosion control practices;
- 632 (h) Construction schedule that includes dates of erosion control practice installation, start of land disturbance and site stabilization;
- 634 (i) Culvert sizes (existing and proposed);
- 635 (j) Any other information necessary to reasonable determine the location, nature and conditions 636 of any physical or environmental features of the site.
- 637 (3) Erosion control performance standards. Proposed design, suggested location and phased
 638 implementation of effective, practicable erosion control measures for plans shall be designed,
 639 engineered and implemented to achieve the following results:
- 640 (a) Prevent gully and bank erosion;
- 641 (b) Limit total off-site permissible annual aggregate soil loss for exposed areas resulting from
- sheet and rill erosion to an annual, cumulative soil loss rate not to exceed 5.0 tons sediment yield
 per acre annually, as determined using the U.S. Natural Resources Conservation Service
- Technical Guide or another commonly accepted soil erosion methodology approved by The Dane
 County Land and Water Resources Department, that considers season of year, site
- 646 characteristics, soil erodibility and slope. Erosion control measures for plan approval need not 647 attempt to regulate soil transportation within the boundaries of the applicant's site.
- (c) Provide stable outlet capable of carrying designed discharge flow as required in s.
 14.12(2)(c), at a non-erosive velocity. Outlet design must consider flow capacity and flow duration. This requirement applies to both the site outlet and the ultimate outlet to stormwater conveyance or waterbody.
- 652 (d) Prevent or reduce all of the following:
- 653 **1.** The deposition of soil from being tracked onto streets by vehicles.
- 654 **2.** The discharge of sediment from disturbed areas into on-site storm water inlets.
- 655 **3.** The discharge of sediment from disturbed areas into adjacent waters of the state.
- 656 **4.** The discharge of sediment from drainage ways that flow off the site.
- **5.** The discharge of sediment by dewatering activities.
- 658 6. The discharge of sediment eroding from soil stockpiles existing for more than 7 days.
- 659 **7.** The transport by runoff of chemicals, cement and other building compounds and materials on
- the construction site during the construction period.
- 661 (4) *Implementation.* The BMPs used to comply with this section shall be implemented as follows:
- (a) Erosion and sediment control practices shall be constructed or installed before land disturbing
- 663 activity begins.

(b) Erosion and sediment control practices shall be maintained until final stabilization.

665 (c) Final stabilization activity shall commence when land disturbing activity ceases and final grade 666 has been reached on any portion of the site.

667 (d) Temporary stabilization activity shall commence when land disturbing activity has temporarily 668 ceased and will not resume for a period exceeding 14 calendar days.

(e) BMPs that are no longer necessary for erosion and sediment control shall be removed.

670 **(5)** *Grading within five (5) feet of property line.* Except as authorized in this section, the topography within five (5) feet of any property line at the commencement of any development shall remain unchanged.

(a) When land disturbing activity associated with development occur within five (5) feet of any property line, finished grades in that area shall be restored to the topography in existence before the land disturbing activity began. A positive slope of one-half (1/2) inch vertical per one (1) foot horizontal within five (5) feet of the property line is allowed to provide proper drainage away from a one or two family residence.

(b) The established grade of the adjoining property shall determine the finished grade at the
property line for any development. The owner of the property under development bears the
burden of proof as to the established grade at the property line and the topography within five (5)
feet of the property line.

(c) Existing drainage ways and drainage easements along property lines shall be maintained
 including, but not limited to, natural watercourses and stormwater management areas shown on
 plats and certified survey maps.

685 (d) Development in Floodplain Districts requiring fill to comply with chapter 17 is exempt from this subsection.

687 (e) The director may authorize grading resulting in changes to the existing topography at and within five (5) feet of any property line, if the following are provided:

689 **1.** The intent of the grading and an explanation of its necessity, and

690 **2.** Documentation showing that stormwater runoff will not negatively affect adjacent properties. 691

692 14.12 STORMWATER MANAGEMENT PLAN REQUIREMENTS.

693 (1) *Plan materials.* Stormwater management plans shall satisfy all of the requirements in 14.12(2), and shall address at a minimum the following information:

695 (a) A narrative describing the proposed project, including implementation schedule for planned practices;

697 (b) Identification of the entity responsible for long-term maintenance of the project;

698 (c) A map showing drainage areas for each watershed area;

699 (d) A summary of runoff peak flow rate calculations, by watershed area, including:

- 700 **1.** Pre-existing peak flow rates;
- 701 **2.** Post-development peak flow rates with no detention;
- 702 **3.** Post-development peak flow rates with detention;

703 **4.** Assumed runoff curve numbers (RCNs); and

704 **5.** Time of concentration (Tc) used in calculations.

(e) A complete site plan and specifications, signed by the person who designed the plan. All plans shall be drawn to an easily legible scale, shall be clearly labeled, and shall include, at a minimum, all of the following information:

708 **1.** Property lines and lot dimensions;

709 **2.** All buildings and outdoor uses, existing and proposed, including all dimensions and 710 setbacks;

All public and private roads, interior roads, driveways and parking lots. Show traffic patterns
 and type of paving and surfacing material;

4. All natural and artificial water features including, but not limited to lakes, ponds, streams (including intermittent streams), and ditches. Show ordinary high water marks of all navigable waters, 100-year flood elevations and delineated wetland boundaries, if any. If not available, appropriate flood zone determination or wetland delineation, or both, may be required at the applicant's expense;

718 **5.** Depth to bedrock;

- 719 6. Depth to seasonal high water table;
- 720 7. The extent and location of all soil types as described in the Dane County Soil Survey, slopes 721 exceeding 12%, and areas of natural woodland or prairie:
- 722 Existing and proposed elevations (referenced to the North American Vertical Datum of 1988, 8. 723 where available) and existing and proposed contours in the area requiring a grading and filling 724 permit:
- 725 9. Elevations, sections, profiles, and details as needed to describe all natural and artificial 726 features of the project:
- 727 10. Soil erosion control and overland runoff control measures, including runoff calculations as 728 appropriate:
- 729 **11.** Detailed construction schedule:
- 730 12. Copies of permits or permit applications required by any other governmental entities or 731 agencies;
- 732 **13.** Any other information necessary to reasonably determine the location, nature and condition 733 of any physical or environmental features;
- 734 14. Location of all stormwater management practices;
- 735 15. All existing and proposed drainage features;
- 736 16. The location and area of all proposed impervious surfaces; and
- 737 17. The limits and area of the disturbed area.
- 738 (f) Engineered designs for all structural management practices;
- 739 (g) A description of methods to control oil and grease or written justification for not providing 740 such control:
- 741 (h) If required under sec. 14.12(2)(f), a description and plans to control temperature of runoff;
- 742 A maintenance plan and schedule for all permanent stormwater management practices as (i) 743 recorded on the affidavit required in sec. 14.10(3)(d).
- 744 A summary of infiltration calculations including: (j)
- 745 Pre-development infiltration volume. 1.
- 746 2. Calculated infiltration volume goal.
- 747 Achieved post-development infiltration volume. 3.
- 748 (k) Flood elevation for the 200-yr design storm and proposed minimum opening elevation.
- 749 Stormwater management performance standards. Proposed design, suggested location (2) 750 and phased implementation of effective, practicable stormwater management measures for plans 751 shall be designed, engineered and implemented to achieve the following results:
 - (a) Sediment control.
- 752 753 For new development, design practices to retain soil particles greater than 5 microns on the 1. 754 site (80% reduction) resulting from a one-year design storm, according to approved procedures, 755 and assuming no sediment resuspension;
- 756 For redevelopment resulting in exposed surface parking and drive areas, design practices to 2. 757 retain soil particles greater than 20 microns on those areas (40% reduction) resulting from a one-758 year design storm, according to approved procedures, and assuming no sediment resuspension. 759 Under no circumstances shall the site's existing sediment control level or trapping efficiency be 760 reduced as a result of redevelopment.
- 761 a. For redevelopment with proposed impervious surface area greater than 80% of existing, the 762 first 0.5 inches of runoff from impervious surfaces must be captured using green infrastructure.
- 763 (b) Oil and grease control. For all commercial or industrial development, and all other uses 764 where the potential for pollution by oil or grease, or both, exists, the first 0.5 inches of runoff must 765 be treated using the best oil and grease removal technology available. This requirement may be 766 waived by the plan reviewer only when the applicant can demonstrate that installation of such 767 practices is unnecessary.
- 768 (c) Runoff rate control
- 769 For new development, design practices to maintain pre-development peak runoff rates for 1. 770 the 1, 2, 10, 100, and 200-year, 24-hour design storms.
- 771 The maximum runoff curve number (RCN) used in such calculations shall be those shown in 2. 772 Table 1. The TR-55-specified curve numbers for other land uses shall be used. Heavily disturbed
- 773 sites will be lowered one permeability class for hydrologic calculations. Lightly disturbed areas, or

- areas where practices have been implemented to restore soil structure to pre-developed conditions, require no modification.
- (d) Outlets. Provide stable outlet capable of carrying designed discharge flow as required in
 sec. 14.51(2)(c), at a non-erosive velocity. Outlet design must consider flow capacity and flow
 duration. This requirement applies to both the site outlet and the ultimate outlet to stormwater
 conveyance or waterbody.
- 780

Table 1. Maximum Pre-development							
Runoff Curve Numbers							
<u>Runoff Curve</u> <u>Number</u>	<u>Hydrologic Soil Group*</u>						
	А	В	С	D			
Woodland	30	55	70	77			
Grassland	39	61	71	78			
Cropland	51	68	78	83			

781 782 783

784

*When dual HSG are specified, the drained condition shall be assumed.

(e) Infiltration.

785 **1.** For new development, design practices to infiltrate sufficient runoff volume so that post-786 development infiltration volume shall be at least 90% of the pre-development infiltration volume, 787 based upon average annual rainfall.

7882. The maximum pre-development runoff curve number (RCN) used in such calculations shall be those shown in Table 1.

790 If, when designing appropriate infiltration systems, more than two percent (2%) of the site is 3. 791 required to be used as effective infiltration area, the applicant may alternately design infiltration 792 systems and pervious surfaces to meet or exceed the annual pre-development recharge rate. 793 The annual pre-development recharge rate shall be determined from the Wisconsin Geological 794 and Natural History Survey's 2009 report, Groundwater Recharge in Dane County, Estimated by 795 a GIS-Based Water-Balanced Model or subsequent updates to this report, or by a site specific 796 analysis using other appropriate techniques. If this alternative design approach is taken, at least 797 two percent (2%) of the site must be used for infiltration.

4. *Pre-treatment.* Before infiltrating runoff, pre-treatment shall be required for parking lot runoff and for runoff from new road construction in commercial, industrial and institutional areas that will enter an infiltration system. The pre-treatment shall conform to the design standards in s. 14.14 and be designed to protect the infiltration system from clogging prior to scheduled maintenance and to protect ground-water quality.

Separation distances. Infiltration practices shall be located so that the characteristics of the soil and the separation distance between the bottom of the infiltration system and the elevation of seasonal high groundwater or the top of competent bedrock are shown in Table 2.

806 6. *Prohibitions*. Infiltration practices may not be installed in any of the following areas:

a. Areas associated with tier 1 industrial facilities identified in sec. NR 216.21(2)(a), Wis.
 Admin. Code, including storage, loading, rooftop and parking.

809 b. Storage and loading areas of tier 2 industrial facilities identified in sec. NR 216.21(2)(b),
 810 Wis. Admin. Code.

811 **c.** Fueling and vehicle maintenance areas.

- 812 813 814 815 **d.** Areas within 1,000 feet up gradient or within 100 feet down gradient of direct conduits to groundwater.

Table 2. Separation Distances and							
Soil Characteristics							
Source Area	Separation	<u>Soil</u>					
Source Area	<u>Distance</u>	Characteristics					
Industrial, Commercial, Institutional Parking Lots and Roads	5 Feet or More	Filtering Layer					
Residential	5 Feet	Filtering					
Arterial Roads	or More	Layer					
Roofs Draining to Subsurface Infiltration Practices	1 Foot or More	Native or Engineered Soil with Particles Finer than Coarse Sand					
Roofs Draining to Surface Infiltration Practices	Not Applicable	Not Applicable					
All Other Impervious Source Areas	3 Feet or More	Filtering Layer					

816 Areas with runoff from industrial, commercial and institutional parking lots and roads and e. 817 residential arterial roads with less than five feet separation distance from the bottom of the 818 infiltration system to the elevation of seasonal high groundwater or the top of bedrock.

819 Areas within 400 feet of a community water system well as specified in sec. NR 811.16(4), f. 820 Wis, Admin, Code, for runoff infiltrated from commercial, industrial and institutional land uses or 821 regional devices for residential development.

822 Areas where contaminants of concern, as defined in sec. NR 720.03(2), Wis. Admin. Code, g. 823 are present in the soil through which infiltration will occur.

824 Alternate use of runoff. Where alternate uses of runoff are employed, such as for toilet 7. 825 flushing, laundry or irrigation, such alternate use shall be given equal credit toward the infiltration 826 volume required by this section.

827 Minimizing groundwater pollution. According to ch. NR 151, Wis. Admin. Code, infiltration 8. 828 systems designed in accordance with this section shall, to the extent technically and 829 economically feasible, minimize the level of pollutants infiltrating to groundwater and shall 830 maintain compliance with the preventive action limit at a point of standards application in 831 accordance with ch. NR 140, Wis. Admin. Code. However, if site-specific information indicates 832 that compliance with the preventive action limit is not achievable, the infiltration system may not 833 be installed or shall be modified to prevent infiltration to the maximum extent practicable.

834 Thermal control. (f)

835 1. The stormwater management plan shall include provisions and practices to reduce the 836 temperature of runoff for sites located within the watershed of a river or stream identified by the 837 Wisconsin Department of Natural Resources as:

838 A Cold Water Community as identified through secs.NR 102.04(3)(a), NR 104, Wisconsin a. 839 Administrative Code, and Class I, Class II, and Class III Trout Streams identified in "Wisconsin 840 Trout Streams," DNR publication PUB-FH-806-2002 or its successor.

841 Rivers or streams proposed by the Wisconsin Department of Natural Resources as Cold b. 842 Water Communities and Class I, II, and III Trout Streams.

843 2. The storm-water management plan does not have to meet the requirement in sec. 14.12(2)(f) if 844 the applicant can justify by use of a model approved by the director, that practices are not 845 necessary because the temperature increase of runoff from the site post-development will be 846 zero

847 3. A current list and maps of affected watersheds shall be available for reference at the office of 848 the local approval authority and the plan review agency.

849 Closed Watersheds. Pre-development modeling must include closed watershed areas. (g) 850 Sites within closed watersheds must be designed to achieve 90% stay-on, without exemption. 851 Sites with areas subject to inundation (ground elevations below the watershed outlet elevation) 852 853 must include:

- 1. a stable outlay capable of handling overflow events.
- 854 2. an emergency drawdown or pumping plan.
- 855 3. storage capacity for back-to-back 100-yr storm events...

856 (3) Stormwater management goals. The following standards shall be met whenever possible, 857 and proposed design, suggested location and implementation of practices to meet these goals 858 shall be included in plans:

859 (a) For existing development, design practices to retain soil particles greater than 40 microns on 860 the site (20% reduction) resulting from a one-year, 24-hour design storm, according to approved 861 procedures, and assuming no sediment resuspension.

862 (b) For street reconstruction, design practices to retain soil particles greater than 20 microns on 863 the site (40% reduction) resulting from a one-year, 24-hour design storm, according to approved 864 procedures, and assuming no sediment resuspension. 865

866 14.13 OFF-SITE STORMWATER MANAGEMENT.

867 (1) The local authority may establish off-site stormwater management and associated fees, 868 provided that provisions are made to manage stormwater by an off-site facility, and provided that 869 all of the following conditions for the off-site facility are met:

870 (a) The facility is in place;

- 871 (b) The facility is designed and adequately sized to provide a level of stormwater control that at 872 least meets the ordinance standards.
- 873 (c) The local approval authority is satisfied that the facility has a legally obligated entity 874 responsible for its long-term operation and maintenance.
- 875 (2) A municipality adopting and administering an ordinance pursuant to sec. 14.05(3) that 876 establishes off-site stormwater management shall adopt the standards for off-site stormwater 877 management set forth in this ordinance. 878
- 879 14.14 TECHNICAL STANDARDS AND SPECIFICATIONS. The design of all best management 880 practices designed to meet the requirements of this chapter shall comply with the following 881 technical standards:
- 882 (1) Natural Resources Conservation Service's "Wisconsin Field Office Technical Guide, 883 Chapter 4" or its successor;
- 884 (2) Applicable construction or erosion control standards by the Wisconsin Department of 885 Natural Resources:
- 886 (3) Any other technical methodology approved by the Dane County Land and Water Resources 887 Department. 888

889 14.15 PERMIT FEES.

- 890 (1) The local approval authority may establish a fee schedule for erosion control and stormwater 891 management permits.
- 892 (2) For areas under Dane County jurisdiction according to sec. 14.05(2) and sec. 14.05 (3)(c) 893 and (d), the erosion control and stormwater management permit fee shall be a \$100 base fee for 894 projects eligible to submit simplified plan materials under sec. 14.10(2)(d). The base fee for other 895 projects subject to the erosion control requirements of sec. 14.06 shall be \$200, and the base fee 896 for projects subject to the stormwater management requirements of sec. 14.07 shall be \$400. 897
 - (a) Permit Revisions. The fee for significant permit revisions shall be the base fee.
- 898 (b) Late filing fee. When an applicant begins work requiring a permit before obtaining the 899 permit or appropriate approvals, the fee shall be doubled.
- 900 (c) Expired permit fee. When an applicant fails to stabilize the site according to the approved 901 permit conditions, an after-the-fact permit is required, and applicable fees shall be doubled.
- 902 (3) The fee for preliminary review letters shall be \$50.
- 903 (a) If a preliminary approval letter has been obtained, the erosion control and stormwater 904 management base fee shall be reduced by \$50.
- 905 (4) For sites required to obtain an erosion control permit under sec. 14.06, there shall be an 906 additional fee of \$.006 per square foot of disturbed area.
- 907 (5) For sites required to obtain a stormwater control permit under sec. 14.07, there shall be an 908 additional fee of \$.015 per square foot of new or redeveloped impervious area.
- 909 (6) Municipal street and road maintenance projects are exempt from fees required in this 910 section. 911

912 14.16 APPEALS.

913 (1) County jurisdiction.

- 914 (a) Any person aggrieved by any decision of the director pursuant to this ordinance may appeal 915 to the Dane County Land Conservation Committee (hereinafter "committee"). Such appeal shall 916 be taken within 30 days after the challenged decision. Notice of Appeal setting forth the specific 917 grounds for the appeal shall be filed with the director and the committee. The director shall 918 forthwith transmit to the committee the record upon which the action appealed from was taken.
- 919 (b) The committee shall fix a reasonable time for the hearing of the appeal and publish a class 2 920 notice thereof under ch. 985, Wis. Stats., as well as give due notice to the parties in interest, and 921 decide the same within a reasonable time. Upon the hearing any party may appear in person or 922 by agent or attorney.
- 923 (c) The committee may, in conformity with the provisions of this ordinance, reverse or affirm, 924 wholly or partly, or modify the order, requirement, decision or determination appealed from and 925 may make such order, requirement, decision or determination as ought to be made, and shall 926 have all the powers of the officer from whom the appeal is taken.

- 927 **(d)** The concurring vote of a majority of the committee shall be necessary to reverse the decision of the director.
- 929 (2) Municipal jurisdiction. A municipality adopting and administering an ordinance pursuant to
 930 sec. 14.05(3), shall be governed by the appeals process described in sec. 62.23(7)(e), Wis. Stats.
 931

932 14.17 VARIANCES.

- 933 (1) An applicant may include in the application a request for a variance from the requirements of
 934 sec. 14.11 or 14.12. No variance shall be granted unless applicant demonstrates and the director
 935 finds that all of the following conditions are present:
- (a) Enforcement of the standards set forth in this ordinance will result in unnecessary hardship
 to the permittee;
- 938 (b) The hardship is due to exceptional physical conditions unique to the property; and
- 939 (c) Granting the variance will not adversely affect the public health, safety or welfare, nor be contrary to the spirit, purpose and intent of this ordinance.
- 941 (2) If all of the conditions set forth in sec. 14.17(1) are met, a variance may only be granted to
 942 the minimum extent necessary to afford relief from unnecessary hardship, with primary
 943 consideration to water quality and impact to downstream conditions.
- 944 (3) A person aggrieved by a variance determination by the director may appeal that decision to 945 the committee pursuant to sec. 14.16.
- (4) A person aggrieved by a decision of the committee regarding a variance may appeal that decision to the board of adjustment pursuant to sec. 10.26.
 948

949 14.18 VIOLATIONS AND ENFORCEMENT.

- 950 (1) Stop work order.
- 951 (a) Whenever the local approval authority finds any noncompliance with the provisions of this 952 ordinance, the local approval authority shall attempt to communicate with the ownerpermittee or 953 person performing the work to obtain immediate and voluntary compliance if such person is 954 readily available. If the ownerpermittee or person performing the work is not readily available, 955 that person refuses to voluntarily comply immediately or the noncompliance presents an 956 immediate danger or will cause or threatens to cause bodily injury or damage to off-site property 957 including, but not limited to, off-site runoff, the local approval authority shall post in a conspicuous 958 place on the premises, a stop work order which shall cause all activity not necessary to correct 959 the noncompliance to cease until noncompliance is corrected.
- 960 **(b)** The stop work order shall provide the following information:
- 961 **1.** date of issuance;
- 962 **2.** town and section number or equivalent information within a municipality;
- 963 **3.** reason for posting; and
- 964 **4.** signature of inspector posting the order.
- 965 (c) Unauthorized removal of a stop work order from the premises shall be a violation of this ordinance.
- 967 (2) In addition to posting a stop work order, the local approval authority shall provide notification
 968 to the <u>permittee</u>, owner <u>if not the permittee</u>, orand contractor by personal service, written notice
 969 by certified mail, electronic mail, or facsimile transmission.
- (a) The permittee and contractor shall have 24 hours from time of notification by the local approval authority to correct any noncompliance with the plan when notification is by either personal communication of noncompliance to the owner or contractor or their respective agents, or written notice sent by certified mail to owner or contractor.
- (b) If notice is not provided under sec. 14.18(2)(a), the permittee shall have 72 hours to correct any noncompliance with the plan when notification is by posting notice in a conspicuous place on the site or sending notice by facsimile transmission to the owner or contractor.
- (3) If the noncompliance is not corrected within the time periods specified in sub. (2)(a) or (b),
 the permittee authorizes the local approval authority to take any action, to perform any work, or
 commence any operations necessary to correct noncompliance on the subject property where
 notice of noncompliance has been issued to bring the property into conformance with plan
 requirements. The permittee and landowner further consent to reimburse the authority for the
 total costs and expenses of the corrective actions. Reimbursement may be collected as a special

983 charge upon the <u>permittee's interest in the property</u> for current services rendered as provided by 984 law.

985
986
986
987
988
988
989
(4) If the permittee has filed an appeal under sec. 14.16(1)(a) prior to the expiration of the time for compliance under sec. 14.18(2)(a) or (b), the local approval authority may take action, perform work or correct conditions only to the extent necessary to protect against an imminent hazard or condition that will cause or threatens to cause personal injury or damage to off-site property.

990 **14.19 PENALTIES**.

(1) Any person, firm, company or corporation who violates or refuses to comply with the
 provisions of this ordinance shall be subject to a forfeiture of not less than \$200 nor more than
 \$1,000 and the costs of prosecution. Each day that a violation exists shall constitute a separate
 offense.

(2) Any person who has the ability to pay any forfeiture entered against him or her under this
ordinance, but refuses to do so, may be confined in the county jail until such forfeiture is paid, but
in no event to exceed thirty days. In determining whether an individual has the ability to pay a
forfeiture, all items of income and all assets may be considered regardless of whether or not such
income or assets are subject to garnishment, lien, or attachment by creditors.

1000
 (3) The corporation counsel is authorized to seek enforcement of any part of this ordinance by court action seeking injunctive relief. It shall not be necessary for the county to seek other remedies before seeking injunctive relief.
 1003

1004
 14.20 INTERPRETATION. In their interpretation and application, the provisions of this ordinance
 shall be held to be minimum requirements and shall be liberally construed in favor of Dane
 County, and shall not be deemed a limitation or repeal of any other power granted by the
 Wisconsin Statutes.

14.21 SEVERABILITY CLAUSE. If any section, provision or portion of this ordinance is ruled invalid by a court, the remainder of the ordinance shall not for that reason be rendered ineffective.

1010 1011 1012

1009

1013 [EXPLANATION: This amendment revises and recodifies the Erosion Control and Stormwater 1014 Management Ordinance after recodification of the Manure Storage Ordinance to Chapter 49.]

1015