Dane County Rezone Petition


 Application Date
 Petition Number

 09/19/2025
 DCPREZ-2025-12213

 11/25/2025
 DCPREZ-2025-12213

OWNER INFORMATION				AGENT INFORMATION					
THOMAS AND RITA BRISKY		PHONE (with Code) (608) 516	lR		AGENT NAME RIVER VALLEY LAND SURVEYING		PHONE (with Code) (608) 434		
BILLING ADDRESS (Numbe		ADDRESS (Number & Street 721 KENNEDY STR							
(City, State, Zip) MAZOMANIE, WI 53560			(City, State, Zip) Sauk City, WI 53583						
			E	E-MAIL	ADDRESS				
ADDRESS/L	OCATION 1	ADDRESS/LOCATION 2			TION 2	ADDRESS/LOCATION 3			
ADDRESS OR LOCA	TION OF REZONE	ADDRESS OR LOCATION OF REZONE			OF REZONE	ADDRESS OR LOCATION OF REZONE			
6683 Dunlap Hollow	Road								
TOWNSHIP ROXBURY	SECTION T	OWNSHIP			SECTION	TOWNSHIP	SECT	ION	
PARCEL NUMBE	RS INVOLVED	PARC	CEL NUMBE	RS IN	VOLVED	PARCEL NUMBE	RS INVOLV	/ED	
0907-311	-8501-0		0907-311	-855′	1-0	0907-304-9002-0			
		RE	EASON FO	R RE	ZONE				
FR	OM DISTRICT:			TO DISTRICT:				ACRES	
FP-35 Farmland Pre	eservation District		RR-2 Rural Residential District			ct		1.5	
RR-2 Rural Residen		FP-35 Farmland Preservation District				1.0			
FP-35 Farmland Preservation District			FP-1 Farmland Preservation District			District		7.7	
C.S.M REQUIRED?	PLAT REQUIRED?		STRICTION JIRED?		INSPECTOR'S INITIALS	SIGNATURE:(Owner	or Agent)		
☑ Yes ☐ No	Yes 🗹 No	Yes 🗹 No		RUH1					
Applicant Initials Applicant Initials Applicant Init			ials	S		PRINT NAME:			
						DATE:			

Form Version 04.00.00



PETITION 12213 THOMAS AND RITA BRISKY

Proposed Zoning Boundary

Tax Parcel Boundary

Feet 0 180 360 720





Zoning Change Application


Zoning Division Room 116, City-County Building 210 Martin Luther King Jr. Blvd. Madison, Wisconsin 53703-3342


Phone: (608) 266-4266 Fax: (608) 267-1540


Items that must be submitted with your application:


- Written Legal Description of the proposed Zoning Boundaries
 Legal description of the land that is proposed to be changed. The description may be a lot in a plat,
 Certified Survey Map, or an exact metes and bounds description. A separate legal description is required for each zoning district proposed. The description shall include the area in acres or square feet.
- Scaled Drawing of the location of the proposed Zoning Boundaries
 The drawing shall include the existing and proposed zoning boundaries of the property. All existing buildings shall be shown on the drawing. The drawing shall include the area in acres or square feet.

Owner's Name Thomas and Rita Brisky			Agent's Name Daniel Marks River Valley Land Surveying			
Address 6683 Dunlop Hollow I			Address Phone	721 Kennedy Street		
Phone	Mazomanie, WI 53560			Sauk City, WI 53583		
Email	(608) 516-3693			(608) 434-3034		
	tom.brisky@gmail.com		Email	danielmarks00@gmail.com		
Town: Ro	oxbury	Parcel numbers affected:	050/0907-311-8	8551-0, 050/0907-311-8501-0, 050/0907-304-9002-0		
Section:_	30	Property address or location	n: Located in	the SW1/4-SE1/4 Sec. 30 & NW1/4-NE1/4 Sec. 31		
Zoning D	istrict change: (To	/ From / # of acres) Being char	nged to mu	ultiple zoning districts		
2012						
O Sepa O Crea O Comp O Othe	ration of buildings tion of a residentia pliance for existing r:					
I authorize	d But	have permission to act on behalf of the o	wner of the prop	Derty. Date: 08/28/2025		









PRELIMINARY CERTIFIED SURVEY MAP

LOCATED IN THE SW1/4 OF THE SE1/4 OF SECTION 30 AND THE NW1/4 OF THE NE1/4 OF SECTION 31, INCLUDING ALL OF LOT 1 OF DANE COUNTY CERITIFED SURVEY MAP NO. 8745, Notes T9N, R7E, TOWN OF ROXBURY, DANE COUNTY, WISCONSIN.

- 1.) Bearings are grid based on the Dane County coordinate system designed by the Wisconsin Department of Transportation NAD 83 (2011). The west line of the NW1/4 of the NE1/4 of Section 31 bears N 00°49'41" E.
- 2.) Surveyor has made no investigation or independent search for easements of record, encumbrances, restrictive covenants, ownership title evidence, or any other facts that an accurate and current title search may disclose.
- 3.) Recorded bearings and distances are shown in parentheses.

Curve Data

#	Radius	Delta	Length	Chord	Chord Bearing	Tan In	Tan Out
1-2	253.35'	34°56'32"	154.50'	152.12'	N 44°10'05" E	N 26°41'51" E	N 61°38'22" E
1-3	253.35'	24°50'55"	109.87'	109.02'	N 39°07'17" E	N 26°41'51" E	N 51°32'45" E
2-3	253.35'	10°05'37"	44.63'	44.57'	N 56°35'34" E	N 51°32'45" E	N 61°38'22" E
4-7	511.46'	42°24'29"	378.57'	369.98'	N 07°33'53.5" W	N 28°46'08" W	N 13°38'21" E
2-4	511.46'	03°09'17"	28.16'	28.16'	N 12°03'42.5" E	N 10°29'04" E	N 13°38'21" E
2-5	511.46'	13°14'34"	118.21'	117.95'	N 03°51'47" E	N 02°45'30" W	N 10°29'04" E
5-6	511.46'	11°32'58"	103.10'	102.93'	N 08°31'59" W	N 14°18'28" W	N 02°45'30" W
6-7	511.46'	14°27'40"	129.09'	128.75'	N 21°32'18" W	N 28°46'08" W	N 14°18'28" W
8-9	679.78'	10°12'59"	121.20'	121.05'	N 18°44'50" E	N 13°38'21" E	N 23°51'20" E
10-11	299.30'	43°33'44"	227.56'	222.12'	N 50°33'00" W	N 72°19'52" W	N 28°46'08" W
12-13	266.30'	41°18'56"	192.03'	187.89'	N 49°25'36" W	N 70°05'04" W	N 28°46'08" W
14-15	332.30'	45°20'34"	262.98'	256.17'	N 51°26'25" W	N 74°06'42" W	N 28°46'08" W
16-17	478.46'	42°24'29"	354.14'	346.11'	N 07°33'53.5" W	N 28°46'08" W	N 13°38'21" E
18-3	544.46'	35°59'58"	342.09'	336.49'	N 10°46'18" W	N 07°13'41" E	N 28°46'08" W
18-19	544.46'	11°09'30"	106.03'	105.87'	N 23°11'23" W	N 28°46'08" W	N 17°36'38" W
19-20	544.46'	10°01'12"	95.22'	95.09'	N 12°36'02" W	N 17°36'38" W	N 07°35'26" W
20-3	544.46'	14°49'16"	140.84'	140.45'	N 00°10'48" W	N 07°35'26" W	N 07°13'50" E
21-22	646.78'	11°30'32"	129.92'	129.70'	N 19°23'37" E	N 13°38'21" E	N 25°08'53" E

Description of Proposed Lot 1 to be Rezoned

A parcel of land located in the SW1/4 of the SE1/4 of Section 30 and the NW1/4 of the NE1/4 of Section 31 including a portion of Lot 1 of Dane County Certified Survey Map No. 8745, T9N, R7E, Town of Roxbury, Dane County, Wisconsin more particularly described as follows:

Commencing at a 3/4" solid round iron rod at the southwest corner of the SW1/4 of the SE1/4 of said Section 30, thence S89°44'42"E along the south line of said SW1/4 of the SE1/4, 734.83 ft. to the point of beginning; thence N44°38'46"W, 63.44 ft. to a 3/4" solid round iron rod; thence N01°13'35"E, 403.88 ft. to a 3/4" solid round iron rod; thence N17°01'43"E, 129.21 ft. to a 3/4" solid round iron rod; thence N18°31'59"E, 116.97 ft. to a 3/4" solid round iron rod; thence N31°21'01"E, 225.59 ft. to the centerline of Dunlop Hollow Road in a curve to the left having a radius of 511.46 ft. and a central angle of 11°32'58"; thence southeasterly along said centerline and the arc of said curve, 103.10 ft., said curve having a long chord bearing S08°31'59"E, 102.93 ft.; thence S31°21'01"W, 139.19 ft. to a 3/4" solid round iron rod; thence S18°31'59"W, 108.69 ft. to a 3/4" solid round iron rod; thence S17°01'43"W, 119.19 ft. to a 3/4" solid round iron rod; thence S01°13'35"W, 320.73 ft. to a 3/4" solid

round iron rod; thence S18°59'05"E, 62.36 ft. to a 3/4" solid round iron rod; thence S61°12'16"E, 363.16 ft. to a 3/4" solid round iron rod; thence S23°51'30"W, 240.99 ft. to a 3/4" solid round iron rod; thence N63°24'00"W, 264.37 ft. to a 3/4" solid round iron rod; thence N13°47'15"E, 156.87 ft. to a 3/4" solid round iron rod; thence N44°38'46"W, 92.57 ft. to the point of beginning.

Surveyor's Certificate

I, Daniel Marks, Professional Land Surveyor, do hereby certify: that I have surveyed and mapped the property shown on this plat of survey under the direction of Tom Brisky and that such map is a correct representation of all the exterior boundaries of the land surveyed and is accurate and correct to the best of my knowledge and belief. This survey was made in compliance with Chapter AE-7 per AE-7.05(8) and is made for the exclusive use of the present owners of the property and those who purchase, mortgage or guarantee the title thereto within one year from the date here on. As to them I warrant the accuracy of said survey and map.

DANIEL A. MARKS
S-3024
MADISON
WI

900 SURVE

Dated this 18th day of August 2025

Daniel Marks

Professional Land Surveyor S-3024 Field work completed 8/7/2025 Sheet 4 of 5



PRELIMINARY CERTIFIED SURVEY MAP

LOCATED IN THE SW1/4 OF THE SE1/4 OF SECTION 30 AND THE NW1/4 OF THE NE1/4 OF SECTION 31, INCLUDING ALL OF LOT 1 OF DANE COUNTY CERITIFED SURVEY MAP NO. 8745, T9N, R7E, TOWN OF ROXBURY, DANE COUNTY, WISCONSIN.

Description of Proposed Lot 2 to be Rezoned to FP-35

A parcel of land located in the SW1/4 of the SE1/4 of Section 30 and the NW1/4 of the NE1/4 of Section 31 including a portion of Lot 1 of Dane County Certified Survey Map No. 8745, T9N, R7E, Town of Roxbury, Dane County, Wisconsin more particularly described as follows:

Beginning at a 3/4" solid round iron rod at the southwest corner of the SW1/4 of the SE1/4 of said Section 30 and the southwest corner of Lot 2 of Dane County Certified Survey Map No. 15771; thence S79°40'12"E along the south line of said Lot 2, 484.51 ft. recorded as (N80°03'53"W and N79°39'50"W, 484.66 ft.) to a 3/4" solid round iron rod at the southeast corner of said Lot 2; thence N15°32'38"E along the east line of said Lot 2, 432.47 ft. (recorded as S15°07'27"W and S15°31'30"W, 432.65 ft.) to a 3/4" solid round iron rod; thence N17°13'26"E along the east line of said Lot 2, 339.21 ft. to a 3/4" solid round iron rod; thence N20°27'58"E (recorded as S20°28'29"W and S20°04'26"W) along the east line of said Lot 2, 116.85 ft. to a 3/4" solid round iron rod; thence N26°41'51"E (recorded as S26°17'48"W) along the east line of said Lot 2, 132.17 ft. to a 3/4" solid round iron rod at the point of curvature of a curve to the right having a radius of 253.35 ft. and a central angle of 34°56'32"; thence northeasterly along the east line of said Lot 2 and the arc of said curve, 154.50 ft. to a 3/4" solid round iron rod located in a curve to the left and in the centerline of Dunlop Hollow Road, said curve having a long chord bearing N44°10'05"E, 152.12 ft.; thence from said point of curvature of a curve to the left having a radius of 511.46 ft. and a central angle of 13°14'34"; thence southerly along said centerline and the arc of said curve, 118.21 ft., said curve having a long chord bearing S03°51'47"W, 117.95 ft.; thence S31°21'01"W, 225.59 ft. to a 3/4" solid round iron rod; thence S18°31'59"W, 116.97 ft. to a 3/4" solid round iron rod; thence S17°01'43"W, 129.21 ft. to a 3/4" solid round iron rod; thence S01°13'35"W, 403.88 ft. to a 3/4" solid round iron rod; thence $544^{\circ}38'46$ "E, 156.01 ft. to a 3/4" solid round iron rod; thence $513^{\circ}47'15$ "W, 156.87 ft. to a 3/4" solid round iron rod; thence $563^{\circ}24'00$ "E, 264.37 ft. to a 3/4" solid round iron rod; thence $563^{\circ}24'00$ "E, 264.37 ft. to a 3/4" solid round iron rod; thence N23°51'30"E, 240.99 ft. to a 3/4" solid round iron rod; thence N61°12'16"W, 363.16 ft. to a 3/4" solid round iron rod; thence N18°59'05"W, 62.36 ft. to a 3/4" solid round iron rod; thence N01°13'35"E, 320.73 ft. to a 3/4" solid round iron rod; thence N17°01'43"E, 119.19 ft. to a 3/4" solid round iron rod; thence N18°31'59"E, 108.69 ft. to a 3/4" solid round iron rod; thence N31°21'01"E, 139.19 ft. to the centerline of Dunlop Hollow Road in a curve to the left having a radius of 511.46 ft. and a central angle of 14°27'40"; thence southeasterly along said centerline and the arc of said curve, 129.09 ft. to the point of tangency thereof, said curve having a long chord bearing \$21°32'18"E, 128.75 ft.; thence \$28°46'08"E along said centerline, 403.98 ft. to a 3/4" solid round iron rod at the point of tangency of a curve to the left having a radius of 299.30 ft. and a central angle of 43°33'44"; thence southeasterly along said centerline and the arc of said curve, 227.56 ft. to the end of said curve on the east line of the SW1/4 of the SE1/4 of said Section 30, said curve having a long chord bearing S50°33'00"E, 222.12 ft.; thence S00°12'42"W along the east line of said SW1/4 of the SE1/4, 161.85 ft. to a 1" inside diameter iron pipe at the northeast corner of the NW1/4 of the NE1/4 of said Section 31; thence S00°40'15"W along the east line of said NW1/4 of the NE1/4, 1,323.41 ft. to a 3/4" solid round iron rod at the southeast corner of said NW1/4 of the NE1/4; thence N89°55'41"W along the south line of said NW1/4 of the NE1/4, 1,322.88 ft. to a 3/4" solid round iron rod at the southwest corner of said NW1/4 of the NE1/4; thence N00°49'41"E along the west line of said NW1/4 of the NE1/4, 1,327.66 ft. to the point of beginning.

Description of Proposed Lot 3 to be Rezoned to FP-1

A parcel of land located in the SW1/4 of the SE1/4 of Section 30, T9N, R7E, Town of Roxbury, Dane County, Wisconsin more particularly described as follows:

Commencing at a 3/4" solid round iron rod at the southwest corner of the SW1/4 of the SE1/4 of said Section 30 and the southwest corner of Lot 1 of Dane County Certified Survey Map No. 15771; thence N00°17'16"E along the west line of the SW1/4 of the SE1/4 of said Section 30 and the west line of said Lot 1, 1320.10 ft. (recorded as 1320.14 ft.) to the northwest corner of said SW1/4 of the SE1/4 and the northwest corner of said Lot 1; thence S89°48'23"E along the north line of said SW1/4 of the SE1/4 and the north line of said Lot 1, 982.07 ft. (recorded as S89°48'41"E, 982.15 ft.) to a 3/4" solid

round iron rod in the centerline of Dunlop Hollow Road at the northeast corner of said Lot 1 and at the point of beginning; thence S89°53'14"E along the north line of said SW1/4 of the SE1/4, 335.37 ft. to a 1" inside diameter iron pipe at $\,$ the northeast corner of said SW1/4 of the SE1/4; thence S00°12'42"W along the east line of said SW1/4 of the SE1/4, 1,160.13 ft. to the centerline of Dunlop Hollow Road in a curve to the right having a radius of 299.30 ft. and a central angle of 43°33'44"; thence northwesterly along said centerline and the arc of said curve, 227.56 ft. to a 3/4" solid round iron rod at the point of tangency thereof, said curve having a long chord bearing N50°33'00"W, 222.12 ft.; thence N28°46'08"W along said centerline, 403.98 ft. to a 3/4" solid round iron rod at the point of curvature of a curve to the right having a radius of $511.46 \; \text{ft.}$ and a central angle of $42^{\circ}24'29"$; thence northerly along said centerline and the arc of said curve, 378.57 ft. to the point of tangency thereof on the east line of Lot 1 of Dane County Certified Survey Map No. 15771, said curve having a long chord bearing N07°33'53.5"W, 369.98 ft.; thence N13°38'21"E (recorded as S13°14'18"W) along said centerline and the east line of said Lot 1, 189.50 ft. to the point of tangency of a curve to the right having a radius of 679.78 ft. and a central angle of 10°12'59"; thence northeasterly along said centerline, the east line of said Lot 1 and the arc of said curve, 121.20 ft. to the point of beginning, said curve having a long chord bearing N18°44'50"E, 121.05 ft.



8/18/2025

Daniel Mu

Sheet 5 of 5

RIVER VALLEY LAND SURVEYING

721 KENNEDY STREET - SAUK CITY - WISCONSIN - 53583 - PHONE (608)643-4391



RR-2 and FP-35 to RR-2 (Proposed Lot 1)

A parcel of land located in the SW1/4 of the SE1/4 of Section 30 and the NW1/4 of the NE1/4 of Section 31 including a portion of Lot 1 of Dane County Certified Survey Map No. 8745, T9N, R7E, Town of Roxbury, Dane County, Wisconsin more particularly described as follows:

Commencing at a 3/4" solid round iron rod at the southwest corner of the SW1/4 of the SE1/4 of said Section 30, thence S89°44′42″E along the south line of said SW1/4 of the SE1/4, 734.83 ft. to the point of beginning; thence N44°38′46″W, 63.44 ft. to a 3/4" solid round iron rod; thence N01°13′35″E, 403.88 ft. to a 3/4" solid round iron rod; thence N17°01′43″E, 129.21 ft. to a 3/4" solid round iron rod; thence N18°31′59″E, 116.97 ft. to a 3/4" solid round iron rod; thence N31°21′01″E, 225.59 ft. to the centerline of Dunlop Hollow Road in a curve to the left having a radius of 511.46 ft. and a central angle of 11°32′58″; thence southeasterly along said centerline and the arc of said curve, 103.10 ft., said curve having a long chord bearing S08°31′59″E, 102.93 ft.; thence S31°21′01″W, 139.19 ft. to a 3/4" solid round iron rod; thence S18°31′59″W, 108.69 ft. to a 3/4" solid round iron rod; thence S17°01′43″W, 119.19 ft. to a 3/4" solid round iron rod; thence S01°13′35″W, 320.73 ft. to a 3/4" solid round iron rod; thence S18°59′05″E. 62.36 ft. to a 3/4" solid round iron rod; thence S61°12′16″E, 363.16 ft. to a 3/4" solid round iron rod; thence S23°51′30″W, 240.99 ft. to a 3/4" solid round iron rod; thence N63°24′00″W, 264.37 ft. to a 3/4" solid round iron rod; thence N13°47′15″E, 156.87 ft. to a 3/4" solid round iron rod; thence N44°38′46″W, 92.57 ft. to the point of beginning.

FP-35 and RR-2 to FP-35 (Proposed Lot 2)

A parcel of land located in the SW1/4 of the SE1/4 of Section 30 and the NW1/4 of the NE1/4 of Section 31 including a portion of Lot 1 of Dane County Certified Survey Map No. 8745, T9N, R7E, Town of Roxbury, Dane County, Wisconsin more particularly described as follows:

Beginning at a 3/4" solid round iron rod at the southwest corner of the SW1/4 of the SE1/4 of said Section 30 and the southwest corner of Lot 2 of Dane County Certified Survey Map No. 15771; thence S79°40'12"E along the south line of said Lot 2, 484.51 ft. recorded as (N80°03'53"W and N79°39'50"W, 484.66 ft.) to a 3/4" solid round iron rod at the southeast corner of said Lot 2; thence N15°32'38"E along the east line of said Lot 2, 432.47 ft. (recorded as S15°07'27"W and S15°31'30"W, 432.65 ft.) to a 3/4" solid round iron rod; thence N17°13'26"E along the east line of said Lot 2, 339.21 ft. to a 3/4" solid round iron rod; thence N20°27'58"E (recorded as S20°28'29"W and S20°04'26"W) along the east line of said Lot 2, 116.85 ft. to a 3/4" solid round iron rod; thence N26°41'51"E (recorded as S26°17'48"W) along the east line of said Lot 2, 132.17 ft. to a 3/4" solid round iron rod at the point of curvature of a curve to the right having a radius of 253.35 ft. and a central angle of 34°56'32"; thence northeasterly along the east line of said Lot 2 and the arc of said curve, 154.50 ft. to a 3/4" solid round iron rod located in a curve to the left and in the centerline of Dunlop Hollow Road, said curve having a long chord bearing N44°10'05"E, 152.12 ft.; thence from said point of curvature of a curve to the left having a radius of 511.46 ft. and a central angle of 13°14'34"; thence southerly along said centerline and the arc of said curve, 118.21 ft., said curve having a long chord bearing SO3°51'47"W, 117.95 ft.; thence S31°21'01"W, 225.59 ft. to a 3/4" solid round iron rod; thence S18°31′59"W, 116.97 ft. to a 3/4" solid round iron rod; thence S17°01'43"W, 129.21 ft. to a 3/4" solid round iron rod; thence S01°13'35"W, 403.88 ft. to a 3/4" solid round iron rod; thence S44°38'46"E, 156.01 ft. to a 3/4" solid round iron rod; thence S13°47'15"W, 156.87 ft. to a 3/4" solid round iron rod; thence S63°24'00"E, 264.37 ft. to a 3/4" solid round iron rod; thence N23°51'30"E, 240.99 ft. to a 3/4" solid round iron rod; thence N61°12'16"W, 363.16 ft. to a 3/4" solid round iron rod; thence N18°59′05″W, 62.36 ft. to a 3/4" solid round iron rod; thence N01°13′35″E, 320.73 ft. to a 3/4" solid round iron rod; thence N17°01'43"E, 119.19 ft. to a 3/4" solid round iron rod;

thence N18°31′59″E, 108.69 ft. to a 3/4" solid round iron rod; thence N31°21′01″E, 139.19 ft. to the centerline of Dunlop Hollow Road in a curve to the left having a radius of 511.46 ft. and a central angle of 14°27′40″; thence southeasterly along said centerline and the arc of said curve, 129.09 ft. to the point of tangency thereof, said curve having a long chord bearing S21°32′18″E, 128.75 ft.; thence S28°46′08″E along said centerline, 403.98 ft. to a 3/4" solid round iron rod at the point of tangency of a curve to the left having a radius of 299.30 ft. and a central angle of 43°33′44″; thence southeasterly along said centerline and the arc of said curve, 227.56 ft. to the end of said curve on the east line of the SW1/4 of the SE1/4 of said Section 30, said curve having a long chord bearing S50°33′00″E, 222.12 ft.; thence S00°12′42″W along the east line of said SW1/4 of the SE1/4, 161.85 ft. to a 1″ inside diameter iron pipe at the northeast corner of the NW1/4 of the NE1/4 of said Section 31; thence S00°40′15″W along the east line of said NW1/4 of the NE1/4, 1,323.41 ft. to a 3/4" solid round iron rod at the southeast corner of said NW1/4 of the NE1/4; thence N89°55′41″W along the south line of said NW1/4 of the NE1/4, 1,322.88 ft. to a 3/4" solid round iron rod at the southwest corner of said NW1/4 of the NE1/4; thence N00°49′41″E along the west line of said NW1/4 of the NE1/4, 1,327.66 ft. to the point of beginning.

FP-35 to FP-1 (Proposed Lot 3)

A parcel of land located in the SW1/4 of the SE1/4 of Section 30, T9N, R7E, Town of Roxbury, Dane County, Wisconsin more particularly described as follows:

Commencing at a 3/4" solid round iron rod at the southwest corner of the SW1/4 of the SE1/4 of said Section 30 and the southwest corner of Lot 1 of Dane County Certified Survey Map No. 15771; thence N00°17′16″E along the west line of the SW1/4 of the SE1/4 of said Section 30 and the west line of said Lot 1, 1320.10 ft. (recorded as 1320.14 ft.) to the northwest corner of said SW1/4 of the SE1/4 and the northwest corner of said Lot 1; thence S89°48′23″E along the north line of said SW1/4 of the SE1/4 and the north line of said Lot 1, 982.07 ft. (recorded as S89°48'41"E, 982.15 ft.) to a 3/4" solid round iron rod in the centerline of Dunlop Hollow Road at the northeast corner of said Lot 1 and at the point of beginning; thence S89°53'14"E along the north line of said SW1/4 of the SE1/4, 335.37 ft. to a 1" inside diameter iron pipe at the northeast corner of said SW1/4 of the SE1/4; thence S00°12'42"W along the east line of said SW1/4 of the SE1/4, 1,160.13 ft. to the centerline of Dunlop Hollow Road in a curve to the right having a radius of 299.30 ft. and a central angle of 43°33'44"; thence northwesterly along said centerline and the arc of said curve, 227.56 ft. to a 3/4" solid round iron rod at the point of tangency thereof, said curve having a long chord bearing N50°33'00"W, 222.12 ft.; thence N28°46'08"W along said centerline, 403.98 ft. to a 3/4" solid round iron rod at the point of curvature of a curve to the right having a radius of 511.46 ft. and a central angle of 42°24′29"; thence northerly along said centerline and the arc of said curve, 378.57 ft. to the point of tangency thereof on the east line of Lot 1 of Dane County Certified Survey Map No. 15771, said curve having a long chord bearing NO7°33′53.5″W, 369.98 ft.; thence N13°38'21"E (recorded as S13°14'18"W) along said centerline and the east line of said Lot 1, 189.50 ft. to the point of tangency of a curve to the right having a radius of 679.78 ft. and a central angle of 10°12′59"; thence northeasterly along said centerline, the east line of said Lot 1 and the arc of said curve, 121.20 ft. to the point of beginning, said curve having a long chord bearing N18°44′50″E, 121.05 ft.